


County Surveyor's Record, Douglas County, Oregon

11648

Dependent Resurvey of part of W. Bdy. of T. 22 S., R. 8 W.

CHAINS
34.30

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for angle point No. 1, with brass cap mkd.



from which

A fir, 44 ins. diam., bears N. 18° 30' E., 34 lks. dist., mkd.
A P 1 S 18 B T.

A maple, 15 ins. diam., bears S. 71° W., 21 lks. dist., mkd.
A P 1 S 13 B T.

37.16


Foot of desc., bears N. 75° E. and S. 75° W.; leave timber and continue over level bottom land, through very scattering undergrowth.

39.80

Proportionate point,

Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

*RECAP SURVEY 1872-1873
BLIND SPOT AT QUINCY
AUG. 12, 1931*



from which

A fir, 8 ins. diam., bears S. 57° 45' E., 292 lks. dist., mkd.
1/4 S 18 B T.

A fir, 48 ins. diam., bears S. 33° 45' W., 370 lks. dist., mkd.
1/4 S 13 B T.


45.37

Proportionate point for the meander cor. on left bank of Umpqua River, falls on a caving bank where a corner would not last and some distance back from the mean high water line.

45.56

Mean high water line on left bank of Umpqua River.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness meander cor. of fracl. secs. 13 and 18, with brass cap mkd.



from which

An alder, 9 ins. diam., bears S. 40° E., 73 lks. dist., mkd.
W C T 22 S R 8 W S 18 M C B T.

An alder, 14 ins. diam., bears S. 54° W., 76 lks. dist., mkd.
W C T 22 S R 9 W S 13 M C B T.

Thence across the Umpqua River.

54.05

Right bank of Umpqua River.

An alder tree, 6 ins. diam., for witness meander cor. of fracl. secs. 13 and 18, 1 mark

M C on S.,
W C T 22 S on N.,
R 8 W S 18 on E., and
R 9 W S 13 on W. side;

from which