

Dependent Resurvey of Subdivisional Lines Bounding Sec. 18

CHAINS

Old bearing tree:

A fir, 60 ins. diam., bears N. 70° W., 59 lks. dist., over-growth has been chopped away and the marks burned off; on a new blaze mark T 22 S R 8 W S 18 B T.

New bearing trees:

A fir, 30 ins. diam., bears N. 11° 30' E., 57 lks. dist., mkd. T 22 S R 8 W S 17 B T.

A fir, 24 ins. diam., bears S. 52° 30' E., 76 lks. dist., mkd. T 22 S R 8 W S 20 B T.

A fir, 20 ins. diam., bears S. 16° 15' W., 56 lks. dist., mkd. T 22 S R 8 W S 19 B T.

Thence

S. 87° 46' W., on a true line, bet. secs. 18 and 19.

Desc. 221 ft. over SW. slope, through dense timber and undergrowth.

28.75 Dry wash, course SW. Asc. 42 ft. over SE. slope.

40.06 Proportionate point,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$   $\frac{S 18}{S 19}$   
1931

from which

A fir, 40 ins. diam., bears N. 36° W., 26 lks. dist., mkd.  $\frac{1}{4}$  S 18 B T.

A fir, 30 ins. diam., bears S. 3° 30' W., 59 lks. dist., mkd.  $\frac{1}{4}$  S 19 B T.

Spur, slopes S. 80° W.; desc. 536 ft. over NW. slope.

60.09 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for W.  $\frac{1}{16}$  sec. cor., with brass cap mkd.

W  $\frac{1}{16}$   $\frac{S 18}{S 19}$   
1931

from which

A hemlock, 12 ins. diam., bears N. 59° W., 32 lks. dist., mkd. W  $\frac{1}{16}$  S 18 B T.

A hemlock, 15 ins. diam., bears S. 41° W., 36 lks. dist., mkd. W  $\frac{1}{16}$  S 19 B T.

77.00 Creek, 4 lks. wide, course N. 30° W.; asc. 367 ft. over NE. slope.

80.54 The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp.

Land, rolling hills.  
Soil, rocky red clay; 3rd rate.  
Timber, fir, cedar, pine, and hemlock.  
Undergrowth, rhododendron, alder, willow, maple, and madrona.

From the cor. of secs. 17, 18, 19, and 20,

N. 3° 55' W., on a true line, bet. secs. 17 and 18.