Dependent Resurvey of Subdivisional Lines Bounding Sec. 18

CHAINS	
	S. 89° 50' W., on a true line, bet. secs. 7 and 18.
	Desc. 116 ft. over W. slope, through dense timber and undergrowth.
2.60	Creek, 1 lk. wide, course NW.; asc. 154 ft. over NE. slope.
7.00	Spur, slopes N.; desc. 239 ft. over W. slope.
15.40	Leave timber and undergrowth, bears N. and S.; thence over rolling bottom land.
38.31	Proportionate point,
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd. ¼ S 7 S 18 1931 from which
	A maple, 12 ins. diam., bears N. 4° W., 362 lks. dist., mkd. ¼ S 7 B T.
	An oak, 18 ins. diam., bears S. 52° 15' E., 13.63 chs. dist., mkd. ¼ S 18 B T.
39.50	Fence, bears NE. and SW.
41.92	Proportionate point,
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for meander cor. of fracl. secs. 7 and 18, with brass cap mkd. T 22 S M C / S 7 S 18 R 8 W 1931 from which
	A cottonwood, 8 ins. diam., bears N. 17° 15' E., 80 lks. dist., mkd. T 22 S R 8 W S 7 M C B T.
	A maple, 20 ins. diam., bears S. 63° 30' W., 151 lks. dist., mkd. T 22 S R 8 W S 18 M C B T.
43.50	Desc. 36 ft. into river bottom, through undergrowth.
44.50	Left bank of Umpqua River, course SW. Thence across the river.
50.59	Proportionate point for the meander cor. of fracl. secs. 7 and 18, falls in the edge of the water on a large bar of exposed bedrock.
52.29	Mean high water line of the right bank of Umpqua River.
	Set an iron post, 3 ft. long, 1 in. diam., on exposed bedrock, supported by a mound of stone, 10 ft. base, 3 ft. high, for witness meander cor. of fracl. secs. 7 and 18, with brass cap mkd. T 22 S S 7 / MC WC S 18 R 8 W. 1931. from which
	An oak, 20 ins. diam., bears N. 26° 45' W., 93 lks. dist., mkd. W C T 22 S R 8 W S 7 M C B T.