

Dependent Resurvey of Portion of S. Bdy. of T. 20 S., R. 10 W.

CHAINS

T 20 S
R 10 W | R 9 W
S 36 | S 31

1918

from which

A fir snag, 30 ins. diam., bears N. 32° W., 63 lks. dist.,
with illegible scribe marks visible on decayed base.
(Record distance, 65 lks.)

The iron post being rusted nearly through, I replace it with an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked

T 20 S.
R 10 W | R 9 W
S 36 | S 31
T 21 S R 10 W S 1
1951

from which new bearing trees

A cedar, 16 ins. diam., bears N. 66½° E., 26 lks. dist.,
marked T 20 S R 9 W S 31 BT.

A cedar, 16 ins. diam., bears N. 57° W., 52 lks. dist.,
marked T 20 S R 10 W S 36 BT.

Deposit the old iron post at the base of the new iron post.

S. 89°00' W., along the S. bdy. of sec. 36, marking and blazing the true line.

Ascend 62 ft. along N. slope, changing to NE. slope, through heavy timber and dense undergrowth.

- 2.55 Top of ascent on N. slope; desc. 18 ft. over NW. slope.
- 3.40 A ravine, course N.; asc. 17 ft. over NE. slope.
- 3.90 A small spur, slopes N. 10° W.; desc. 12 ft. over NW. slope.
- 4.90 A ravine, course N. 15° E.; asc. 107 ft. over NE. slope.
- 7.50 A spur, slopes N. 5° E.; desc. 60 ft. over NW. slope.
- 9.65 The head of a ravine, course N. 5° E.; asc. 112 ft. over NE. slope.
- 12.40 A spur, slopes N. 15° W.; desc. 97 ft. over NW. slope.
- 14.35 A branch, 2 lks. wide, course N. 10° W.; asc. 153 ft. over NE. slope.
- 18.40 A spur, slopes NE.; desc. 131 ft. over NW. slope.
- 22.60 A wet ravine, course N. 30° W.; asc. 49 ft. over NE. slope.
- 24.75 A spur, slopes N.; desc. 76 ft. over NW. slope.
- 26.70 A ravine, course N.; asc. 36 ft. over NE. slope.
- 28.40 Top of ascent on N. slope; desc. 160 ft. over NW. slope.
- 35.30 A branch, 2 lks. wide, course N. 20° E.; asc. 38 ft. over NE. slope.
- 36.06 The ¼ sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., 8 ins. above ground, firmly set, with brass cap marked

¼ S 36
1918