

Dependent Resurvey of Portion of S. Bdy. of T. 20 S., R. 10 W.

CHAINS

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

½ S 35

1951

from which new bearing trees

A hemlock, 20 ins. diam., bears N. 45½° E., 69 lks. dist., marked ½ S 35 BT.

A hemlock, 24 ins. diam., bears N. 54½° W., 140 lks. dist., marked ½ S 35 BT.

Deposit the old iron post at the base of the new iron post.

N. 89°58' W., beginning new measurement.

Descend 130 ft. over gentle W. slope, changing to NW. slope.

5.75 A ravine, course SW.; asc. 15 ft. over SE. slope.

8.00 Top of ascent on S. slope; desc. 410 ft. over SW. slope, changing to W. slope.

27.30 Enter heavy timber and dense undergrowth; edges bear N. 30° W. and SE.

30.95 Dailey Creek, 15 lks. wide, course N. 5° W.; asc. 95 ft. over E. slope, changing to N. slope.

34.50 Ravine, course NE.; asc. 50 ft. over E. slope in fern opening; edges of heavy timber and dense undergrowth bear NE. and South.

36.53 The cor. of secs. 34 and 35, monumented with an iron post, 2 ins. diam., 10 ins. above ground, firmly set, with brass cap marked

T 21 S R 10 W

S 34 | S 35

1918

from which 1918 bearing trees

A fir, 30 ins. diam., bears N. 26° E., 117 lks. dist., plainly blazed and healed. (Record bearing, N. 25° E.)

A fir, 30 ins. diam., bears N. 8° W., 184 lks. dist., plainly blazed and healed.

and 1892 bearing tree

A fir, 60 ins. diam., bears S. 36½° E., 381 lks. dist., bearing a plain old blaze, but no scribe marks visible and these may have been cut out when cor. was changed to refer only to secs. in T. 20 S., R. 10 W.

The old iron post is rusted nearly through; in its place

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 20 S R 10 W

S 34 | S 35

T 21 S R 10 W

S 2

1951

Deposit old iron post at base of new iron post.