

11670 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of S. Bdy. of T. 20 S., R. 10 W.

CHAINS

1/4 S 34

1951

*FD OK 11/18/51
H. PIESKE
M 95-59 A:0*

from which a new bearing tree

A fir, 36 ins. diam., bears N. 8 1/2° E., 97 lks. dist., marked 1/4 S 34 BT.

Deposit the old iron post at the base of the new iron post.

S. 85°20' W., beginning new measurement.

Ascend 110 ft. over E. slope.

4.75 A spur, slopes NE.; desc. 25 ft. over NW. slope.

5.68 The 1/4 sec. cor. of sec. 3, T. 21 S., R. 10 W., monumented with an iron post, 1 in. diam., the top rusted off 6 ins. above ground, with brass cap marked

1/4 S 3

1919

from which the 1919 bearing trees

A maple, 12 ins. diam., bears S. 22° E., 20 lks. dist., with blaze cleanly healed.

A cascara, 10 ins. diam., bears S. 64° W., 68 lks. dist., with no scribe marks remaining on old blaze. (Record bearing, S. 56° W.)

In place of the old post, set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

1/4 S 3

1951

*FD OK 11/18/51
H. PIESKE
M 95-59 A:0*

from which a new bearing tree

A fir, 10 ins. diam., bears S. 41 1/4° W., 30 lks. dist., mkd. 1/4 S 3 BT.

Deposit the old post at the base of the new iron post.

S. 89°21' W., beginning new measurement.

Descend 38 ft. over NW. slope.

1.05 The head of a ravine, course NW.; asc. 17 ft. over NE. slope.

2.00 A small spur, slopes N.; desc. 10 ft. over NW. slope.

3.30 The head of a ravine, course N.; asc. 83 ft. over NE. slope.

5.70 A spur ridge, bears N. 20° W. and S. 20° E.; desc. 350 ft. over W. slope.

12.40 A wet ravine, course SW.; desc. 150 ft. along steep S. slope, changing to SW. slope.

18.50 An intermittent stream, 4 lks. wide, course NW.; asc. 200 ft. over NE. slope.

24.50 A spur, slopes N. 15° W.; desc. 290 ft. over W. slope.

33.05 A branch, 2 lks. wide, course N. 55° W.; asc. 10 ft. over NE. slope.