

Dependent Resurvey of the E. Bdy. of T. 20 S., R. 10 W.

CHAINS 27.10	A branch, 1 lk. wide, course NE.; asc. 50 ft. over SE. slope.										
29.50	Top of ascent on E. slope; desc. 20 ft. over NE. slope.										
31.30	A branch, 1 lk. wide, course S. 40° E.; asc. 330 ft. over SW. slope, changing to S. slope.										
39.57	The cor. of secs. 7, 12, 13 and 18, marked by the decayed stump of a cascara tree, 10 ins. diam., from which A dead alder, 16 ins. diam., bears N. 61½° E., 37 lks. dist., marked T 20 S R 9 W S 7 BT, on decayed blaze. (An 1891 bearing tree.) An alder, 16 ins. diam., bears S. 69° E., 58 lks. dist., marked T 20 S R 9 W S 18 BT on the bark. (A 1921 bearing tree.) A dead fir, 36 ins. diam., bears S. 30° E., 37 lks. dist., marked T 20 S R 9 W S 18 BT on bark blaze. (An 1891 bearing tree; record bearing, S. 35° E.) A fir, 55 ins. diam., bears N. 30° W., 45 lks. dist., marked T 20 S R 10 W S 12 BT on bark blaze. (A 1921 bearing tree.) At the corner point Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr><td colspan="2" style="text-align: center;">T 20 S</td></tr> <tr><td style="text-align: center;">R 10 W</td><td style="text-align: center;">R 9 W</td></tr> <tr><td style="text-align: center;">S 12</td><td style="text-align: center;">S 7</td></tr> <tr><td style="text-align: center;">S 13</td><td style="text-align: center;">S 18</td></tr> <tr><td colspan="2" style="text-align: center;">1952</td></tr> </table> from which new bearing trees, A hemlock, 8 ins. diam., bears N. 71° E., 71 lks. dist., marked T 20 S R 9 W S 7 BT. A hemlock, 12 ins. diam., bears S. 56° W., 33 lks. dist., marked T 20 S R 10 W S 13 BT. Land, mountainous. Soil, sandy loam. Timber, fir, hemlock, cedar, alder and maple. Undergrowth, vine maple, salmonberry, evergreen huckleberry, hazel, arrowwood, and rhododendron.	T 20 S		R 10 W	R 9 W	S 12	S 7	S 13	S 18	1952	
T 20 S											
R 10 W	R 9 W										
S 12	S 7										
S 13	S 18										
1952											
	N. 11°23' W., along the E. bdy. of sec. 12. Ascend 70 ft. over S. slope, through heavy timber and dense undergrowth.										
3.10	Top of ascent on broad spur ridge, bears E. and W.; desc. 15 ft. across spur ridge.										
5.10	End of gradual descent; desc. 300 ft. over NE. slope, changing to steep N. slope.										
11.90	A ravine, course N. 75° E.; asc. 105 ft. over SE. slope.										
15.30	A spur, slopes E.; desc. 11¼ ft. over N. slope.										
17.60	A ravine, course N. 80° E.; thence along E. slope.										
17.80	A ravine, course E.; asc. 115 ft. over broken SE. slope.										
25.10	A ravine, course S. 30° E.; asc. 260 ft. over S. slope.										
30.03	The ¼ sec. cor. of sec. 12, monumented with an iron post, 1 in. diam., 8 ins. above ground, firmly set, with brass cap marked										