

Dependent Resurvey of a Portion of the N. Bdy. of T. 20 S., R. 10 W.

CHAINS

(Restoring the 1892 survey by Nathaniel Martin)

The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., has been remonumented with a steel machine bolt, 5 ft. long, 3/4 in. diam., firmly driven 18 ins. in the ground, from which

A fir, 34 ins. diam., bears N. 35° E., 33 lks. dist., plainly blazed and healed. (A 1922 bearing tree.)

An alder, 18 ins. diam., bears S. 2 1/2° E., 42 lks. dist., marked T 20 S R 10 W S 4 BT in the bark. (A 1922 bearing tree)

A fir, 34 ins. diam., bears S. 85° W., 15 lks. dist., with blaze nearly healed. (An 1892 bearing tree.)

A dead fir, 20 ins. diam., bears N. 77° W., 46 lks. dist., with blaze partly healed and decayed. (An 1892 bearing tree; record distance, 45 lks.)

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 19 S	R 10 W
S 32	S 33
S 5	S 4
T 20 S	
1952	

from which new bearing trees,

A fir, 26 ins. diam., bears S. 20° E., 101 lks. dist., marked T 20 S R 10 W S 4 BT.

A fir, 24 ins. diam., bears N. 27° 45' W., 109 lks. dist., marked T 19 S R 10 W S 32 BT.

Reset the steel machine bolt alongside the iron post.

S. 89° 15' E., bet. secs. 4 and 33, marking and blazing the true line.

Ascend 323 ft. over W. slope, through heavy timber and dense undergrowth.

- 8.16 A ridge, bears N. and S.; desc. 87 ft. over E. slope.
 - 9.85 A creek, 8 lks. wide, course N. 10° W.; asc. 438 ft. over W. slope.
 - 20.17 A ridge, bears N. and S.; desc. 30 ft. over gradual NE. slope.
 - 23.10 A branch, 1 lk. wide, course NW.; asc. 52 ft. over gradual SW. slope.
 - 30.30 Top of ascent on rolling ridge top, bears N. 20° W. and S. 20° E.; desc. 104 ft. over NE. slope.
 - 37.18 Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

1/4 S 33
4 S 4
1952

from which

A fir, 55 ins. diam., bears N. 75° E., 144 lks. dist., marked 1/4 S 33 BT.

See also
 FO. 15
 Rev. Vol. 1
 Pg. 16