

Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 10 W.

CHAINS
37.39

Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked



from which

A hemlock, 24 ins. diam., bears S. 33° E., 41 lks. dist., marked $\frac{1}{4}$ S 36 BT.

A hemlock, 12 ins. diam., bears S. 23° W., 73 lks. dist., marked $\frac{1}{4}$ S 35 BT.

Descend 126 ft. over NW. slope.

44.25 A branch, 1 lk. wide, course NW.; asc. 8 ft. over SW. slope.

45.65 A spur, slopes N. 53° W.; desc. 45 ft. over gradual NW. slope.

50.60 Top of bluff, bears N. 60° W. and S. 60° E.; desc. 300 ft. over bluff.

54.80 Left bank of Smith River, course N. 62° W.

56.80 Right bank of Smith River; asc. 151 ft. over gentle S. slope, changing to SW. slope, through logged area.

57.85 A telephone line, extends N. 67 $\frac{1}{2}$ ° W. and S. 67 $\frac{1}{2}$ ° E.

58.05 A gravelled road, bears N. 67 $\frac{1}{2}$ ° W. and S. 67 $\frac{1}{2}$ ° E.

58.45 A fence, extends N. 67 $\frac{1}{2}$ ° W. and S. 67 $\frac{1}{2}$ ° E.

58.70 A power line, extends N. 60° W. and S. 60° E.


74.49 The corner of secs. 25, 26, 35 and 36, determined at the record bearing and distance from the original NE. bearing tree, as follows:

A fir, 60 ins. diam., bears N. 50° E., 20 lks. dist., with partial scribe marks visible on old bark blaze.

A sawed fir stump, 70 ins. diam., bears S. 67° E., 26 lks. dist., at the record position of the original SE. bearing tree, which was described as a fir, 4 ins. diam.; the stump shows traces of a bark blaze on the NW. face, and a count of the annual rings shows that it was approximately 40 ins. diam. in 1867, rather than 4 ins.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked



*FD. OK 10/84
BY R. STOUTZNER
M 97-80*

from which new bearing trees

A fir, 80 ins. diam., bears S. 12° E., 140 lks. dist., marked T 20 S R 10 W S 36 BT.

A maple, 16 ins. diam., bears S. 12° W., 69 lks. dist., marked T 20 S R 10 W S 35 BT.