

Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 10 W.

CHAINS	
	An alder, 16 ins. diam., bears N. 75°15' W., 48 lks. dist., marked T 20 S R 10 W S 26 BT.
	Land, mountainous and rolling. Soil, sandy loam. Timber, fir, hemlock, cedar, maple and alder. Undergrowth, vine maple, evergreen huckleberry, salmonberry, hazel, arrowwood and salal.
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp. S. 89°46' W., bet. secs. 25 and 36.
	Descend 89 ft. over NW. slope, through heavy timber and dense undergrowth.
2.70	A branch, 3 lks. wide, course S. 30° W.; asc. 146 ft. over SE. slope, changing to E. slope.
6.85	East shoulder of spur, which slopes S.; asc. 4 ft. along S. slope.
9.15	West shoulder of spur; desc. 109 ft. over SW. slope.
12.30	A small ravine, course S. 30° W.; desc. 58 ft. along broken S. slope, changing to SW. slope.
18.90	A small ravine, course SE.; asc. 81 ft. over SE. slope.
21.90	A spur, slopes SW.; desc. 201 ft. over NW. slope, changing to bluffly W. slope.
25.60	A branch, 2 lks. wide, course S. 30° W.; asc. 310 ft. over SE. slope.
35.50	A spur, slopes S. 10° W.; desc. 28 ft. over W. slope.
36.345	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked
	$\begin{array}{r} \frac{1}{4} \text{ S } 25 \\ \frac{1}{4} \text{ S } 36 \\ \hline 1951 \end{array}$
	from which
	A fir, 22 ins. diam., bears N. 63° E., 32 lks. dist., marked $\frac{1}{4}$ S 25 BT.
	A fir, 16 ins. diam., bears S. 80° E., 28 lks. dist., marked $\frac{1}{4}$ S 36 BT.
	Descend 21 ft. over W. slope.
37.00	A ravine, course S.; asc. 166 ft. over E. slope.
41.50	A spur, slopes S. 25° W.; desc. 235 ft. over W. slope.
46.80	A ravine, course S. 30° W.; asc. 117 ft. over SE. slope.
50.70	A spur, slopes SW.; desc. 426 ft. over W. slope.
59.90	A branch, 3 lks. wide, course S.; the bare rock channel of this stream is 25 lks. wide; asc. 208 ft. over E. slope.
63.80	A spur, slopes S. 10° E.; desc. 188 ft. over SW. slope, along N. edge of logged area.
72.69	The cor. of secs. 25, 26, 35 and 36.

PD. 10/18/84
 R. STANTZNER
 N 97-80