

Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 10 W.

CHAINS	
	<p>Land, mountainous. Soil, sandy loam. Timber, fir, hemlock, cedar, maple, alder, chinquapin, madrona, cascara and cherry. Undergrowth, vine maple, hazel, arrowwood, slickleaf, evergreen huckleberry, red huckleberry, manzanita, poison oak and salal.</p> <hr/> <p>N. 3°20' W., bet. secs. 25 and 26. Along W. slope, through heavy timber and dense undergrowth.</p>
2.40	The dry bed of a stream, 5 lks. wide, course S. 30° W.; asc. 400 ft. over SE. slope.
14.50	A spur, slopes S. 20° W.; asc. 50 ft. along W. slope, changing to broken SW. slope.
33.00	A ravine, course SW.; asc. 200 ft. over S. slope.
37.30	A spur, slopes SW.; desc. 4 ft. along W. slope.
37.495	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked</p> <div style="text-align: center;"> $\frac{1}{4}$ S 26 S 25 1951 </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 36° E., 15 lks. dist., marked $\frac{1}{4}$ S 25 BT.</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears S. 55$\frac{1}{2}$° W., 39 lks. dist., marked $\frac{1}{4}$ S 26 BT.</p> <p>Along broken W. slope.</p>
38.10	A fir, 60 ins. diam., on line, mkd. with two hacks each on N. and S. sides.
39.50	A ravine, course SW.; asc. 150 ft. over S. slope.
44.20	A ridge, the divide bet. Smith River and Spencer Creek, at W. side of a small saddle, bears N. 70° W. and S. 70° E.; desc. 320 ft. over NE. slope.
53.00	A branch, 2 lks. wide, course NW.; asc. 130 ft. over SW. slope.
58.00	Top of ascent on W. slope; desc. 300 ft. over NW. slope, changing to steep N. slope.
63.50	An intermittent creek, 10 lks. wide, course N. 80° W.; asc. 220 ft. over S. slope.
69.00	A spur, slopes S. 20° W.; asc. 131 ft. over SW. slope, changing to S. slope.
74.99	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked</p>