

# 11706 County Surveyor's Record, Douglas County, Oregon

## Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 10 W.

CHAINS

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

$$\begin{array}{r} T\ 20\ S\ R\ 10\ W \\ \hline S\ 15\ | S\ 14 \\ \hline S\ 22\ | S\ 23 \\ 1951 \end{array}$$

from which

A cedar, 30 ins. diam., bears N. 38° E., 27 lks. dist., marked T 20 S R 10 W S 14 BT.

A maple, 8 ins. diam., bears S. 52½° E., 2½ lks. dist., marked T 20 S R 10 W S 23 BT.

A crooked maple, 10 ins. diam., bears S. 45° W., 5 lks. dist., marked T 20 S R 10 W S 22 BT.

A fir, 36 ins. diam., bears N. 7° W., 18 lks. dist., marked T 20 S R 10 W S 15 BT.

Land, mountainous.

Soil, sandy loam.

Timber, fir, hemlock, cedar, alder and maple.

Undergrowth, evergreen huckleberry, vine maple, hazel, salmonberry, rhododendron and arrowwood.

From the cor. of secs. 13, 14, 23 and 24.

N. 87°48' W., bet. secs. 14 and 23.

Ascend 60 ft. over steep NE. slope, through heavy timber and dense undergrowth.

1.55 Point of a spur, slopes N. 10° E.; desc. 15 ft. over N. slope.

2.85 A ravine, course N. 10° E.; asc. 112 ft. over NE. slope.

5.65 A spur, slopes N.; desc. 440 ft. over W. slope, changing to broken SW. slope.

20.45 The dry bed of a stream, 5 lks. wide, course N. 50° W.; asc. 20 ft. over NE. slope.

22.10 Point of a spur, slopes N. 15° W.; desc. 10 ft. over NW. slope.

22.80 The dry bed of a stream, 4 lks. wide, course N.; asc. 150 ft. over NE. slope.

28.45 A spur, slopes N.; desc. 160 ft. over NW. slope, changing to W. slope.

32.35 A ravine, course N. 10° W.; desc. 70 ft. over broken NW. slope, changing to N. slope.

40.52 Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$$\begin{array}{r} \frac{1}{4} \frac{S\ 14}{S\ 23} \\ 1951 \end{array}$$

from which

An alder, 20 ins. diam., bears N. 79° W., 67 lks. dist., marked ¼ S 14 BT.

An alder, 16 ins. diam., bears S. 53° E., 31 lks. dist., marked ¼ S 23 BT.