

Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 10 W.

CHAINS

- 24.60 A ravine, course E.; asc. 18 ft. over SE. slope.
- 25.60 Top of ascent on E. slope; desc. 120 ft. over NE. slope.
- 31.50 A ravine, course E.; asc. 25 ft. over SE. slope.
- 32.40 A spur, slopes N. 75° E.; desc. 25 ft. over NE. slope.
- 33.25 A ravine, course E.; asc. 40 ft. over SE. slope.
- 35.80 Top of ascent on E. slope; desc. 50 ft. over NE. slope.
- 37.10 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked
- | | | |
|------|---------------|------|
| | $\frac{1}{4}$ | |
| S 10 | | S 11 |
| | 1952 | |
- from which
- A hemlock, 10 ins. diam., bears S. 40° E., 48 lks. dist., marked $\frac{1}{4}$ S 11 BT.
- A fir, 40 ins. diam., bears S. 12° W., 53 lks. dist., marked $\frac{1}{4}$ S 10 BT.
- Descend 55 ft. over steep N. slope.
- 38.00 A ravine, course N. 80° E.; asc. 230 ft. over S. slope.
- 43.40 A spur, slopes E.; desc. 60 ft. over NE. slope.
- 46.00 A ravine, course S. 75° E.; asc. 170 ft. over SE. slope.
- 51.40 A ridge, bears N. 80° E. and S. 80° W.; desc. 280 ft. over NW. slope.
- 60.75 A spur, slopes NW.; desc. 250 ft. over N. slope.
- 65.20 An intermittent branch, with bare rock bottom, 8 lks. wide, course N. 80° E.; asc. 255 ft. over broken SE. slope, changing to E. slope.
- 74.20 Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked
- | | |
|---------------|--|
| T 20 S R 10 W | |
| S 3 S 2 | |
| S 10 S 11 | |
| 1952 | |
- from which
- A fir, 40 ins. diam., bears N. 71°45' E., 44 lks. dist., marked T 20 S R 10 W S 2 BT.
- A yew, 7 ins. diam., bears S. 34° E., 41 lks. dist., marked T 20 S R 10 W S 11 BT.
- A fir, 40 ins. diam., bears S. 27 $\frac{1}{4}$ ° W., 30 lks; dist., marked T 20 S R 10 W S 10 BT.
- A yew, 6 ins. diam., bears N. 37° W., 75 lks. dist., marked T 20 S R 10 W S 3 BT.