

Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 10 W.

<p>CHAINS 61.70</p> <p>65.30</p> <p>75.75</p> <p>82.61</p> <p>0.30</p> <p>2.65</p> <p>13.00</p> <p>13.83</p> <p>20.10</p> <p>20.30</p> <p>21.07</p> <p>25.21</p> <p>26.49</p>	<p>Spur, slopes S. 30° W.; desc. 20 ft. along broken W. slope.</p> <p>Foot of descent; asc. 375 ft. over SW. slope, changing to S. slope.</p> <p>A ridge, bears E. and W.; desc. 322 ft. over N. slope, changing to steep broken NW. slope.</p> <p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp.</p> <p>Land, mountainous. Soil, sandy loam. Timber, fir, hemlock, cedar, alder and maple. Undergrowth, salmonberry, evergreen huckleberry, vine maple, hazel, rhododendron, thimbleberry, elder and arrowwood.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.</p> <p>N. 2°51' E., bet. secs. 33 and 34.</p> <p>Descend 15 ft. over NE. slope, through heavy timber and dense undergrowth.</p> <p>A branch, 2 lks. wide, course N. 55° W.; asc. 52 ft. over SW. slope.</p> <p>A spur, slopes N. 70° W.; desc. 282 ft. over NW. slope.</p> <p>Edge of bottom, bears NE. and SW.; desc. 6 ft. over gentle NW. slope.</p> <p>The dry bed of a stream, 4 lks. wide, course N. 80° W.; desc. 6 ft. across bottom.</p> <p>A ravine, course N. 80° W.; asc. 5 ft. over S. slope.</p> <p>Point for the meander cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, and in a mound of stone to top, with brass cap marked</p> <div style="text-align: center;"> </div> <p>from which</p> <p>A double willow, 48 ins. diam., bears N. 41° E., 14 lks. dist., marked T 20 S R 10 W S 34 MC BT.</p> <p>An alder, 20 ins. diam., bears S. 56½° W., 65 lks. dist., marked T 20 S R 10 W S 33 MC BT.</p> <p>Descend 27 ft. over steep, gravelly bank.</p> <p>Left bank of Smith River, course S. 30° W.; thence in river near left bank.</p> <p>Left bank of Smith River; asc. 14 ft. over sandy bank.</p> <p>Point for the meander cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, and in a mound of stone to top, with brass cap marked</p>
---	---

FD. 012 8/92  
L. ROBERTS M115-64