

Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 10 W.

CHAINS

T 20 S R 10 W  
S 33 | S 34

M C  
1951

from which

A willow, 9 ins. diam., bears S. 24°45' E., 84 lks. dist., marked T 20 S R 10 W S 34 MC BT.

An alder, 15 ins. diam., bears N. 14½° W., 239 lks. dist., marked T 20 S R 10 W S 33 MC BT.

Descend 4 ft. over gravel bank.

26.62 A ravine, course W.; asc. 5 ft. over SW. slope.

27.00 Thence across bottom meadow; asc. 20 ft. over gentle SW. slope.

38.96 Edge of bottom, bears N. 15° W. and SE.; asc. 29 ft. over SW. slope, through heavy timber and dense undergrowth.

40.60 The ¼ sec. cor. of secs. 33 and 34, located at the record bearing and distance from the stump of the original NW. bearing tree, as follows:

A rotten fir stump, 54 ins. diam., bears N. 60° W., 11 lks. dist., sawed off flush with the ground on uphill side, with no blaze remaining; Ray Dailey says that his father saw this stump when it had scribe marks, but that it was sawed off lower so that a log could be rolled over it by use of a jack screw.

An uprooted alder, 30 ins. diam., bears N. 28° W., 21 lks. dist. a rotted blaze facing the cor. shows possible traces of scribe marks; to the side of blaze under cover of dirt are old axe marks seeming to be a figure 4; higher on the trunk and more recent are marks in bark ¼ S and X. Ray Dailey says that Charles M. Collier, U. S. Cadastral Engineer, retraced the S. ½ mi. bet. secs. 33 and 34, in 1918, while checking position of cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp. At that time he marked this alder to perpetuate the ¼ sec. cor. of secs. 33 and 34; I find no record of the retracement, but the blazes agree for age.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, and in a mound of stone to top, with brass cap marked

*Find OK 8/92  
L. ROBERTS M115-64*

¼  
S 33 | S 34  
1951

from which new bearing trees

A double maple, 36 ins. diam., bears S. 35°45' E., 62 lks. dist., marked ¼ S 34 BT.

An alder, 24 ins. diam., bears S. 47°45' W., 35 lks. dist., marked ¼ S 33 BT.

N. 1°47' W., beginning new measurement.

Ascend 130 ft. over SW. slope.

3.40 A graded trail, bears N. 15° W. and S. 15° E.