

Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 10 W.

CHAINS

- 6.45 A tractor road, bears N. 30° W. and S. 30° E.
- 23.50 Top of ascent on W. slope; desc. 170 ft. over NW. slope, over partly cleared land.
- 32.12 A power line, bears N. 79°45' E. and S. 79°45' W.
- 35.45 A dirt wagon road, bears N. 80° W. and S. 80° E.
- 37.30 A wire fence, bears N. 75° W. and S. 75° E. along edge of bottom land; thence across bottom.
- 40.92 Point for the cor. of secs. 27, 28, 33 and 34, at proportionate distance longitudinally, with latitudinal position controlled by unofficial monumentation on line bet. secs. 28 and 33 and the restored cor. of secs. 26, 27, 34 and 35. (See page 75.)

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap marked

T 20 S R 10 W
S 28 S 27
S 33 S 34
1951

from which

The corner post of an old fence, 1 1/2 ins. diam., bears N. 7° E., 102 lks. dist.

A fir, 22 ins. diam., bears S. 4 1/2° E., 402 lks. dist., marked T 20 S R 10 W S 34 BT.

A fir, 30 ins. diam., bears S. 10°45' W., 393 lks. dist., marked T 20 S R 10 W S 33 BT.

A white warning sign post at S. edge of road, bears N. 22 1/2° W.

From this point the iron tip of a pitchfork handle, 1/2 in. diam., 4 ins. above ground, firmly in place, bears N. 88°48' W., 9.34 chs. dist., an unofficial monumentation on line bet. secs. 28 and 33.

From the same point the cor. of secs. 29, 30, 31 and 32, bears N. 89°49' W., 157.19 chs. dist., monumented with a sandstone, 16 x 12 x 5 ins., firmly set 10 ins. in the ground, marked with 1 notch on S. edge, the E. edge being crumbled, and located at the intersection of old blazed lines. The original bearing tree is gone.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 20 S R 10 W
S 30 S 29
S 31 S 32
1951

from which new bearing trees

A fir, 22 ins. diam., bears N. 34 1/2° E., 44 lks. dist., marked T 20 S R 10 W S 29 BT.

A fir, 24 ins. diam., bears S. 87° E., 75 lks. dist., marked T 20 S R 10 W S 32 BT.

A cedar, 10 ins. diam., bears S. 49° W., 12 lks. dist., marked T 20 S R 10 W S 31 BT.

A fir, 24 ins. diam., bears N. 1 1/2° W., 59 lks. dist., marked T 20 S R 10 W S 30 BT.

Reset the sandstone alongside the iron post.