


Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 10 W.

CHAINS
63.60 A wire fence and telephone line, bear N. 60° W. and S. 60° E.;
thence across open pasture.

66.25 Point for the witness cor. to the meander cor. of secs. 27 and 34.
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground,
with brass cap marked



from which

An alder, 12 ins. diam., bears S. 41° E., 51 lks. dist.,
marked with an X at breast height and the letters BT at the
base.

An ash, 8 ins. diam., bears N. 60°45' W., 166 lks. dist.,
marked with an X at breast height and the letters BT at the
base

The witness cor. is located at the top of a bank sloping SW., with
bedrock exposed; desc. 10 ft. over bank.


66.80 Right bank of Smith River, course N. 60° W.

67.50 True point for the meander cor. of secs. 27 and 34, at proportionate
distance, falls in river; there is no remaining evidence of the
original corner.

68.90 Left bank of Smith River; asc. 22 ft. over sandy bank sloping NE.

71.24 Point for the meander cor. of secs. 27 and 34, at proportionate
distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground,
with brass cap marked



from which

A maple, 60 ins. diam., bears S. 5° E., 726 lks. dist.,
marked T 20 S R 10 W S 34 MC BT.

A cor. of fences extending S. 63° E. and S. 33° W., bears
S. 28° W., 7 lks. dist.

Across level bottom.

78.83 The cor. of secs. 27, 28, 33 and 34.

Land, mountainous, rolling and level.
Soil, sandy and rocky loam.

Timber, fir, hemlock, cedar, maple, alder, dogwood, cascara and ash.
Undergrowth, vine maple, evergreen huckleberry, salmonberry, hazel,
slickleaf and salal.

N. 0°08' E., bet. secs. 27 and 28.

Across open bottom.

1.50 Top of sandy bank sloping N.; desc. 18 ft. over bank.