

Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 10 W.

CHAINS  
2.50.

Point for the meander cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

M C	
S 28	S 27
T 20 S R 10 W	
1951	

from which

A crooked alder, 18 ins. diam., bears S. 43°45' E., 15 lks. dist., marked T 20 S R 10 W S 27 MC BT.

Descend 4 ft. over sandy bank.

2.85 Left bank of Smith River, course W. on bend to SW.

4.05 Right bank of Smith River; asc. 20 ft. over S. slope.

4.715 Point for meander cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

T 20 S R 10 W
S 28   S 27
M C
1951

from which

An alder, 12 ins. diam., bears S. 60½° E., 19 lks. dist., marked T 20 S R 10 W S 27 MC BT.

An ash, 24 ins. diam., bears S. 78¼° W., 61 lks. dist., marked T 20 S R 10 W S 28 MC BT.

Ascend 50 ft. over S. slope through pasture.

6.50 Wire fence and telephone line, bear N. 66° E. and S. 66° W.

6.75 A gravelled road, bears N. 66° E. and S. 66° W.

7.45 Wire fence, bears N. 66° E. and S. 66° W.; asc. 180 ft. over steeper S. slope, through heavy timber and dense undergrowth.

13.30 Point of spur, slopes SE.; asc. 190 ft. over broken SE. slope.

17.65 A spur, slopes E.; desc. 40 ft. over NE. slope.

23.40 A ravine, course SE.; asc. 340 ft. over S. slope.

29.35 A spur, slopes E.; desc. 200 ft. over N. slope.

33.90 A ravine, course N. 60° E.; asc. 70 ft. over SE. slope.

36.30 A spur, slopes N. 80° E.; desc. 25 ft. over NE. slope.

37.72 Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

¼
S 28   S 27
1951