

Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 10 W.

CHAINS  
70.40

A spur, slopes NW.; desc. 130 ft. over NE. slope.

74.34

Point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance; there is no remaining evidence of the original corner

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

|                |
|----------------|
| T 20 S R. 10 W |
| S 16   S 15    |
| -----          |
| S 21   S 22    |
| 1952           |

from which

An alder, 16 ins. diam., bears N.  $43\frac{1}{2}^\circ$  E., 21 lks. dist., marked T 20 S R 10 W S 15 BT.

A fir, 54 ins. diam., bears S.  $63\frac{1}{2}^\circ$  E., 76 lks. dist., marked T 20 S R 10 W S 22 BT.

An alder, 18 ins. diam., bears S.  $70^\circ$  W., 51 lks. dist., marked T 20 S R 10 W S 21 BT.

A fir, 60 ins. diam., bears N.  $61^\circ$  W., 86 lks. dist., marked T 20 S R 10 W S 16 BT.

Land, mountainous.

Soil, sandy loam.

Timber, fir, hemlock; cedar; alder; and maple.

Undergrowth, vine maple, rhododendron, evergreen huckleberry, hazel, salmonberry, salal, arrowwood and manzanita.

From the corner of secs. 14, 15, 22 and 23.

West, bet. secs. 15 and 22.

Descend 400 ft. over NW. slope near top of spur, changing to W. slope, through heavy timber and dense undergrowth.

11.40 An intermittent creek, 30 lks. wide, course S.  $20^\circ$  E.; asc. 160 ft. over E. slope, changing to broken NE. slope.

15.50 The head of a ravine, course N.  $70^\circ$  E.; asc. 300 ft. over E. slope.

23.10 A spur, slopes N.  $30^\circ$  E.; asc. 50 ft. along broken N. slope.

29.50 A spur ridge, bears S.  $73^\circ$  E. and W.; asc. 60 ft. along spur ridge.

35.00 Spur ridge, bears E. and S.  $78^\circ$  W.; asc. 100 ft. over NE. slope, near top of spur ridge,

40.625 Spur ridge, bears N.  $70^\circ$  W. and S.  $70^\circ$  E.

Point for the  $\frac{1}{4}$  sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

|                    |
|--------------------|
| $\frac{1}{4}$ S 15 |
| -----              |
| S 22               |
| 1952               |

from which

A hemlock, 20 ins. diam., bears N.  $3^\circ 45'$  W., 13 lks. dist., marked  $\frac{1}{4}$  S 15 BT.

A hemlock, 28 ins. diam., bears S.  $70^\circ$  E., 69 lks. dist., marked  $\frac{1}{4}$  S 22 BT.