

11726 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 10 W.

CHAINS	
1.70	A small spur, slopes N. 15° W.; desc. 326 ft. over NE. slope.
8.65	A ravine, course NW.; asc. 63 ft. over SW. slope.
10.90	A small spur, slopes N. 50° W.; desc. 136 ft. over N. slope.
13.50	Georgia Creek, 20 lks. wide, course S. 50° W.; asc. 395 ft. over S. slope.
22.30	A spur, from N. 5° E., shoulders of which slope S. 10° E. and S. 15° W. from this point; asc. 145 ft. over SW. slope near top of spur.
28.20	Recross spur, from N. 10° W., slopes S. 5° E.; asc. 50 ft. over SE. slope near top of spur.
30.45	Top of ascent on E. slope; desc. 42 ft. over NE. slope.
36.25	The head of a ravine, course SE.; asc. 60 ft. over S. slope.
37.17	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked
	$\frac{1}{4}$ $S \quad 9 \quad \quad S \quad 10$ 1952
	from which
	A fir, 30 ins. diam., bears S. 87° E., 66 lks. dist., marked $\frac{1}{4}$ S 10 BT.
	A maple, 14 ins. diam., bears S. 29 $\frac{1}{2}$ ° W., 19 lks. dist., marked $\frac{1}{4}$ S 9 BT.
	Ascend 154 ft. over S. slope.
40.00	A spur, slopes S. 20° E.; asc. 10 ft. over SE. slope.
42.05	A ridge, bears NE. and SW.; desc. 7 ft. along W. slope.
44.20	Foot of descent on W. slope; asc. 71 ft. over SW. slope.
47.70	A spur, slopes NW.; desc. 390 ft. over N. slope, changing to NE. slope.
56.26	A ravine, course N. 50° W.; asc. 70 ft. over SW. slope.
58.85	A spur, slopes N. 70° W.; desc. 86 ft. over N. slope.
60.40	A ravine, course S. 80° W.; asc. 275 ft. over SW. slope, changing to S. slope.
67.00	A ridge, bears N. 60° W. and S. 60° E.; desc. 2 ft. over NE. slope.
67.60	A spur, slopes NE.; desc. 192 ft. over N. slope, changing to NE. slope.
72.15	A ravine, course E., on bend to NE.; asc. 40 ft. over SE. slope, changing to E. slope.
74.34	Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked