

11730 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 10 W.

CHAINS									
	<p>An alder, 16 ins. diam., bears N. 62° E., 56 lks. dist., marked $\frac{1}{4}$ S 16 BT.</p> <p>A maple, 30 ins. diam., bears S. 76$\frac{1}{2}$° E., 156 lks. dist., marked $\frac{1}{4}$ S 21 BT.</p> <p>Ascend 175 ft. over NE. slope.</p>								
44.90	A spur, slopes N. 10° E.; desc. 290 ft. over NW. slope.								
54.90	An intermittent stream, 15 lks. wide, course N.; asc. 90 ft. over NE. slope.								
57.70	A spur, slopes N. 20° E.; desc. 60 ft. along N. slope.								
63.80	A ravine, course N. 25° E.; asc. 180 ft. over NE. slope.								
69.70	A spur, slopes N. 10° W.; desc. 180 ft. over NW. slope.								
74.00	An intermittent stream, 8 lks. wide, course N. 10° E.; asc. 247 ft. over E. slope.								
79.50	A spur, slopes N. 30° E.; desc. 10 ft. along N. slope.								
80.84	<p>The cor. of secs. 16, 17, 20 and 21, remonumented by the county surveyor with an iron pipe, 1 in. diam., 14 ins. above ground, firmly in place, from which an original bearing tree,</p> <p>An alder, 32 ins. diam., bears N. 17° W., 40 lks. dist., with partial scribe marks visible on decayed face of partly opened blaze.</p> <p>and trees marked by the county surveyor,</p> <p>A fir, 66 ins. diam., bears N. 52°45' E., 200 lks. dist., marked on the bark S 16 T 20 S R 10 W CS BT.</p> <p>A fir, 31 ins. diam., bears S. 51° E., 110 lks. dist., with partial scribe marks visible on partly healed blaze.</p> <p>An uprooted fir, 28 ins. diam., the stump hole of which bears S. 85° W., 67 lks. dist., with blaze on trunk marked T 20 S R 10 W CS BT.</p> <p>At the corner point</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 20 S R 10 W</td> <td></td> </tr> <tr> <td>S 17 S 16</td> <td></td> </tr> <tr> <td style="border-top: 1px solid black;">S 20 S 21</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1951</td> </tr> </table> </div> <p>from which new bearing trees</p> <p>A fir, 30 ins. diam., bears N. 58$\frac{1}{2}$° E., 197 lks. dist., marked T 20 S R 10 W S 16 BT.</p> <p>A fir, 30 ins. diam., bears S. 69$\frac{1}{4}$° E., 129 lks. dist., marked T 20 S R 10 W S 21 BT.</p> <p>A cherry, 16 ins. diam., bears S. 12$\frac{1}{2}$° W., 49 lks. dist., marked T 20 S R 10 W S 20 BT.</p> <p>Reset the county surveyor's iron pipe alongside the iron post.</p> <p>The sec. cor. is located at the head of a ravine on a steep very brushy N. slope.</p>	T 20 S R 10 W		S 17 S 16		S 20 S 21			1951
T 20 S R 10 W									
S 17 S 16									
S 20 S 21									
	1951								