

Dependent Resurvey of Portion of Subdivisional Lines of T. 20 S., R. 10 W.

CHAINS

At the corner point.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 20 S R 10 W
S 8   S 9
S 17   S 16
1951

from which new bearing trees

A fir, 38 ins. diam., bears N. 35°45' E., 50½ lks. dist., marked T 20 S R 10 W S 9 BT.

A fir, 18 ins. diam., bears S. 25° E., 16 lks. dist., marked T 20 S R 10 W S 16 BT.

A fir, 16 ins. diam., bears S. 20° W., 13 lks. dist., marked T 20 S R 10 W S 17 BT.

A fir, 22 ins. diam., bears N. 32° W., 31½ lks. dist., marked T 20 S R 10 W S 8 BT.

Land, mountainous.

Soil, sandy loam.

Timber, fir, hemlock, cedar, alder, maple and dogwood.

Undergrowth, vinemaple, salmonberry, evergreen huckleberry, hazel, rhododendron, salal and arrowwood.

N. 0°31' E., bet. secs. 8 and 9, along plainly blazed old line of the age of Thiel's survey.

Ascend 37 ft. over S. slope, through heavy timber and dense undergrowth.

0.93 A ridge, bears S. 80° E. and West; desc. 207 ft. over N. slope.

6.63 A branch, 2 lks. wide, course W.; asc. 110 ft. over SW. slope, changing to gradual SE. slope.

20.85 Top of ascent on E. slope; desc. 158 ft. over NE. slope.

26.10 A branch, 4 lks. wide, course N. 70° W.; asc. 209 ft. over S. slope through dense undergrowth in old logged area.

33.14 A spur ridge, bears N. 80° W. and S. 80° E.; desc. 265 ft. over steep N. slope, through scattering timber and dense undergrowth.

38.48 A creek, 12 lks. wide, course W.; asc. 64 ft. over S. slope.

39.85 The ¼ sec. cor. of secs. 8 and 9, monumented with a sandstone, 6 x 3 x 2 ft. above ground, with plain chisel marks on SW. face.

At a point against the W. face of the corner stone, ½ lk. from the old chisel marks,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

¼
S 8   S 9
1952

from which

A maple, 40 ins. diam., bears N. 86° E., 68 lks. dist., marked ¼ S 9 BT.

*Fl. by HINTZ  
Apr. 83  
M 90-42*