

11762 County Surveyor's Record, Douglas County, Oregon

Subdivisions of Sections 7, 8, 9, 10, 11 and 12, T. 27 S., R. 2 W.

CHAINS 79.36	<p>Intersect the closing cor. bet. secs. 8 and 9 set by me August 5, 1905.</p> <p>(79.36 Intersect E. and W. line, 105 lks. E. of cor. of secs. 4, 5, 8 and 9, already described (see Book "C"). I destroy marks on post and bearing trees referring to secs. 8 and 9 and at point of intersection</p> <p>Set a basalt stone, 17 x 12 x 4 ins., 13 ins. in the ground, for closing cor. of secs. 8 and 9, mkd. CC on S. face, with 5 grooves on S. and 4 grooves on E. face; from which</p> <p style="padding-left: 40px;">An alder, 14 ins. diam., bears S. 60° E., 26 lks. dist., mkd. T 27 S R 2 W S 9 BT.</p> <p style="padding-left: 40px;">A maple, 8 ins. diam., bears S. 23° W., 70 lks. dist., mkd. T 27 S R 2 W S 8 BT.</p> <p style="text-align: right;">August 5, 1905)</p> <p>Thence I run</p> <p>S. 0°03' E., on a true line, bet. secs. 8 and 9.</p> <p>Descend through scattering timber and dense undergrowth.</p> <p>0.10 Spring branch, 3 lks. wide, course S. 10° W.</p> <p>12.85 Spring branch, 3 lks. wide, course East.</p> <p>39.36 Set a basalt stone, 12 x 8 x 7 ins., 9 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face; from which</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 22° E., 37 lks. dist., mkd. $\frac{1}{4}$ S 9 BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 66° W., 35 lks. dist., mkd. $\frac{1}{4}$ S 8 BT.</p> <p>I destroy old $\frac{1}{4}$ sec. cor. and marks on bearing trees.</p> <p>51.86 Wagon road to Peel, bears SW. and NE.</p> <p>52.36 Little River, 200 lks. wide, course SW.</p> <p>55.00 Begin ascent of steep rocky ridge, bears S. 10° W.</p> <p>74.35 Summit of spur, bears E. and W.</p> <p>79.36 The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 0°04' W., on a random line, bet. secs. 7 and 8.</p> <p>40.00 Set temp. $\frac{1}{4}$ sec. cor.</p> <p>80.00 Intersect at cor. of secs. 5, 6, 7 and 8, already described (See Book "C"). Thence I run</p> <p>S. 0°04' E., on a true line, bet. secs. 7 and 8.</p> <p>Descend through scattering timber and dense undergrowth, over broken and rocky ground, sloping S.</p> <p>40.00 Set a basalt stone, 14 x 10 x 10 ins., 10 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face; from which</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 88° E., 96 lks. dist., mkd. $\frac{1}{4}$ S 8 BT.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 20° W., 67 lks. dist., mkd. $\frac{1}{4}$ S 7 BT.</p>
-----------------	---