

County Surveyor's Record, Douglas County, Oregon

11770

4

Dependent Resurvey of Sec. 9, T. 29 S., R. 7 W.

CHAINS 12.79	Ravine, drains N.; asc. 175 ft. over broken NE. slope.
19.51	Point for the east 1/16 sec. cor. of secs. 9 and 16. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked <div style="text-align: center;"> $E \frac{1}{16} \frac{S 9}{S 16}$ 1955 </div> from which A fir, 12 ins. diam., bears N. 32° W., 41 lks. dist., marked E 1/16 S 9 BT. A fir, 7 ins. diam., bears S. 34° W., 63 lks. dist., marked E 1/16 S 16 BT. Ascend 266 ft. over broken NE. slope.
28.93	Ridge, bears N. and S. 10° E.; desc. 90 ft. over SW. slope.
36.44	Spur, slopes S. 10° W.; desc. 86 ft. over W. slope.
39.02	Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked <div style="text-align: center;"> $\frac{1}{4} \frac{S 9}{S 16}$ 1955 </div> from which A fir, 18 ins. diam., bears N. 30° W., 25 lks. dist., marked ¼ S 9 BT. A fir, 10 ins. diam., bears S. 74° W., 24 lks. dist., marked ¼ S 16 BT. Descend 76 ft. over SW. slope.
40.54	Ravine, drains S. 20° W.; asc. 66 ft. over SE. slope.
50.25	Spur, slopes W.; desc. 115 ft. over SW. slope.
58.53	Point for west 1/16 sec. cor. of secs. 9 and 16. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked <div style="text-align: center;"> $W \frac{1}{16} \frac{S 9}{S 16}$ 1955 </div> from which A white oak, 9 ins. diam., bears N. 5° W., 4 lks. dist., marked W 1/16 S 9 BT. A pine, 12 ins. diam., bears S. 60½° E., 13 lks. dist., marked W 1/16 S 16 BT. Descend 391 ft. over NW. slope.
75.24	Draw, drains S. 35° W.; asc. 36 ft. over SE. slope.
77.12	Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.
78.04	The cor. of secs. 8, 9, 16 and 17, perpetuated with an iron post, 1 in. diam., 8 ins. above ground, with brass cap marked