

Dependent Resurvey of Sec. 9, T. 29 S., R. 7 W.

CHAINS

COUNTY SURVEYOR

S 8 | S 9  
 S 17 | S 16  
 1954

All bearing trees have been destroyed by logging operations.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 29 S R 7 W  
 S 8 | S 9  
 S 17 | S 16  
 1955

FD OK 2/93  
 BY BENTZ M116-49

from which

A walnut, 6 ins. diam., bears N. 52 $\frac{1}{4}$ ° E., 118 lks. dist., marked T 29 S R 7 W S 9 BT.

A black oak, 30 ins. diam., bears S. 16 $\frac{1}{2}$ ° E., 264 lks. dist., marked T 29 S R 7 W S 16 BT.

A white oak, 8 ins. diam., bears S. 39° W., 153 lks. dist., marked T 29 S R 7 W S 17 BT.

A madrona, 9 ins. diam., bears N. 28° W., 105 lks. dist., marked T 29 S R 7 W S 8 BT.

Reset the 1 in. post alongside the 2 in. post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, oak, maple and madrona.

Undergrowth, vine maple, arrowwood, poison oak and fern.

N. 11° 17' E., bet. secs. 8 and 9.

Ascend 318 ft. over SE. slope, through timber and undergrowth.

17.51 Point for the south 1/16 sec. cor. of secs. 8 and 9.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

S 1/16  
 S 8 | S 9  
 1955

from which

A madrona, 10 ins. diam., bears N. 44° E., 55 lks. dist., marked S 1/16 S 9 BT.

A white oak, 27 ins. diam., bears N. 40° W., 57 lks. dist., marked S 1/16 S 8 BT.

Ascend 32 ft. over SE. slope.

19.38 Ridge, bears NE. and SW.; desc. 279 ft. over NW. slope.

35.02 The  $\frac{1}{4}$  sec. cor. of secs. 8 and 9, perpetuated with an iron rod, 5/8 in. diam., 6 ins. above ground, set by the County Surveyor in 1954.

from which bearing trees marked by Frank Cain in 1913.