

# 11772 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Sec. 9, T. 29 S., R. 7 W.

CHAINS

A fir, 36 ins. diam., bears S.  $65\frac{1}{2}^{\circ}$  E., 95 lks. dist., marked with a healed blaze.

A turned out fir, 30 ins. diam., bears S.  $40^{\circ}$  W., 10 lks. dist., marked with a healed blaze.

and bearing trees marked by the County Surveyor in 1954.

A fir, 8 ins. diam., bears N.  $87^{\circ}$  E., 47 lks. dist., marked  $\frac{1}{4}$  S 9 CS BT.

A fir, 6 ins. diam., bears S.  $80^{\circ}$  W., 20 lks. dist., marked  $\frac{1}{4}$  S 8 CS BT.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 8 \text{ | S } 9 \\ \hline 1955 \end{array}$$

from which new bearing trees

A fir, 25 ins. diam., bears S.  $42\frac{1}{2}^{\circ}$  E., 50 lks. dist., marked  $\frac{1}{4}$  S 9 BT.

A fir, 22 ins. diam., bears S.  $60^{\circ}$  W., 33 lks. dist., marked  $\frac{1}{4}$  S 8 BT.

Reset the rod alongside the iron post.

N.  $0^{\circ}07'$  W., beginning new measurement.

Descend 296 ft. over NW. slope.

11.01 Intersect S. bdy. of donation land claim No. 40, at proportionate distance.

At the intersection point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$$\begin{array}{c} \text{C } 40 \\ \hline \text{S } 8 \text{ | S } 9 \\ \text{T } 29 \text{ S } \text{ R } 7 \text{ W} \\ \text{C } \text{ C} \\ \hline 1955 \end{array}$$

from which

A fir, 48 ins. diam., bears S.  $49^{\circ}$  E., 63 lks. dist., marked L 5 T 29 S R 7 W S 9 CC BT.

A fir, 18 ins. diam., bears S.  $34^{\circ}$  W., 36 lks. dist., marked T 29 S R 7 W S 8 CC BT.

From this corner the point for the SE. corner of donation land claim No. 40 bears S.  $86^{\circ}41'$  E., 22.04 chs. dist., located by record ties; there is no remaining evidence of the original corner.

From the same corner the point for the SW. corner of donation land claim No. 40 bears N.  $86^{\circ}41'$  W., 27.96 chs. dist., located by record ties; there is no remaining evidence of the original corner.