

Dependent Resurvey, Portion of South Bdy., T. 31 S., R. 5 W.

CHAINS

A red fir, 30 ins. diam., bears N. 52° W., 15 lks. dist., with marks S 3 uncovered.

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground, with brass cap marked

T 31 S R 5 W
S 33 S 34
S 4 S 3
T 32 S
1955

from which new bearing trees

A red fir, 20 ins. diam., bears N. 13½° E., 58 lks. dist., marked T 31 S R 5 W S 34 BT.

A red fir, 30 ins. diam., bears S. 68½° E., 74 lks. dist., marked T 32 S R 5 W S 3 BT.

A red fir, 35 ins. diam., bears S. 34° W., 81 lks. dist., marked T 32 S R 5 W S 4 BT.

A red fir, 33 ins. diam., bears N. 66° W., 73 lks. dist., marked T 31 S R 5 W S 33 BT.

Deposit basalt stone alongside the iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, maple, cedar and madrona; undergrowth, huckleberry, vine maple, arrowwood and hazel.

Dependent Resurvey, Portion of Subdivisional Lines, T. 31 S., R. 5 W.
(Restoring the 1882 survey of W. H. Byars)

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.

N. 0°54' E., bet. secs. 35 and 36.

Ascend 401 ft. over SW. slope, through timber and undergrowth.

12.00 Spur, slopes SE.; asc. 178 ft. over SE. slope.

27.58 Ridge, bears NE. and SW.; desc. 300 ft. over NW. slope.

38.70 Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap marked

¼
S 35 S 36
1955

*Ed. 7/73 - BLM
Admin. Survey - SEE
GIS FILE*

from which

A red fir, 12 ins. diam., bears S. 80° E., 130 lks. dist., marked ¼ S 36 BT.

A red fir, 14 ins. diam., bears N. 79° W., 31 lks. dist., marked ¼ S 35 BT.

Descend 712 ft. over NE. slope.

55.78 Branch, 2 lks. wide, course N. 80° W.; asc. 181 ft. over SW. slope.