

Dependent Resurvey, Portion of Subdivisional Lines, T. 31 S., R. 5 W.

CHAINS  
69.54

Top of ascent on W. slope; desc. 254 ft. over NW. slope.

77.40

The cor. of secs. 25, 26, 35 and 36, determined at record bearing and distance from the original SE. bearing tree:

A turned-out fir, 24 ins. diam., bears S. 35° E., 29 lks. dist., with marks BT uncovered.

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground, with brass cap marked

T 31	S R 5 W
S 26	S 25
S 35	S 36
1955	

from which new bearing trees

A red fir, 24 ins. diam., bears N. 47° E., 6 lks. dist., marked T 31 S R 5 W S 25 BT.

A red fir, 32 ins. diam., bears S. 51° E., 55 lks. dist., marked T 31 S R 5 W S 36 BT.

A red fir, 32 ins. diam., bears S. 62½° W., 111 lks. dist., marked T 31 S R 5 W S 35 BT.

A red fir, 23 ins. diam., bears N. 43½° W., 27 lks. dist., marked T 31 S R 5 W S 26 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, maple, cedar and madrona; undergrowth, vine maple, huckleberry, arrowwood and hazel.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp. N. 0°42' E., bet. secs. 34 and 35.

Ascend 8 ft. over SW. slope, through timber and undergrowth.

2.19

Top of ascent on W. slope; desc. 384 ft. over NW. slope.

22.03

Spur, slopes N. 40° W.; desc. 125 ft. over N. slope.

25.07

Branch, 1 lk. wide, course N. 50° W.; asc. 27 ft. over SW. slope.

28.62

Top of ascent on W. slope; desc. 163 ft. over NW. slope.

38.90

The ¼ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap marked

1	
4	
S 34	S 35
1955	

*CS 42/404  
This Cor. moved  
in 1966*

from which

A red fir, 22 ins. diam., bears S. 31° E., 62 lks. dist., marked ¼ S 35 BT.

A red fir, 17 ins. diam., bears S. 72° W., 37 lks. dist., marked ¼ S 34 BT.