

Dependent Resurvey, Portion of Subdivisional Lines, T. 31 S., R. 5 W.

CHAINS

Descend 58 ft. over NW. slope.

42.00 Stream, 20 lks. wide, course NE.; asc. 129 ft. over SE. slope.

49.65 Spur, slopes E.; desc. 122 ft. over NE. slope.

52.27 Ravine, drains S. 80° E.; asc. 385 ft. over S. slope.

61.99 Top of ascent on SE. slope; asc. 133 ft. along E. slope.

77.80 Point for the cor. of secs. 26, 27, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground, with brass cap marked

T 31 S R 5 W
S 27 S 26
S 34 S 35
1955

*SEE 42/404
THIS CORNER MARKED
IN 1966*

from which

A red fir, 10 ins. diam., bears N. 48° E., 24 lks. dist., mkd. T 31 S R 5 W S 26 BT.

A white fir, 5 ins. diam., bears S. 72° E., 17 lks. dist., mkd. T 31 S R 5 W S 35 BT.

A white fir, 10 ins. diam., bears S. 86½° W., 20 lks. dist., mkd. T 31 S R 5 W S 34 BT.

A white fir, 4 ins. diam., bears N. 30° W., 34 lks. dist., mkd. T 31 S R 5 W S 27 BT.

From this point the cor. of secs. 22, 23, 26 and 27, bears N. 1°03' W., 77.81 chs. dist., determined at record bearing and distance from the original SE. bearing tree:

A fir, 32 ins. diam., bears S. 45° E., 30 lks. dist., with marks BT uncovered.

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground, with brass cap marked

T 31 S R 5 W
S 22 S 23
S 27 S 26
1955

from which new bearing trees

A white fir, 20 ins. diam., bears N. 61° E., 90 lks. dist., marked T 31 S R 5 W S 23 BT.

A red fir, 30 ins. diam., bears S. 14° E., 35 lks. dist., marked T 31 S R 5 W S 26 BT.

A red fir, 20 ins. diam., bears S. 31° W., 43 lks. dist., marked T 31 S R 5 W S 27 BT.

A red fir, 30 ins. diam., bears N. 68° W., 35 lks. dist., marked T 31 S R 5 W S 22 BT.

From the same point the cor. of secs. 27, 28, 33 and 34, bears N. 89°58' W., 79.78 chs. dist., determined at record bearing and distance from the remaining original bearing trees: