

Dependent Resurvey, Portion of Subdivisional Lines, T. 31 S., R. 5 W.

CHAINS

A cedar, 48 ins. diam., bears S. 78° E., 75 lks. dist.,
marked T 31 S R 5 W S 34 BT on bark.

A fir, 50 ins. diam., bears N. 36° W., 56 lks. dist.,
with marks S 28 BT remaining on bark.

At corner point

Set an iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground,
with brass cap marked

T 31 S R 5 W
S 28 S 27
S 33 S 34
1955

from which new bearing trees

A red fir, 25 ins. diam., bears N. 76½° E., 48 lks. dist.,
marked T 31 S R 5 W S 27 BT.

A hemlock, 15 ins. diam., bears S. 24° E., 84 lks. dist.,
marked T 31 S R 5 W S 34 BT.

A red fir, 15 ins. diam., bears S. 35° W., 71 lks. dist.,
marked T 31 S R 5 W S 33 BT.

A sugar pine, 20 ins. diam., bears N. 26° W., 62 lks. dist.,
marked T 31 S R 5 W S 28 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, maple, cedar and madrona; undergrowth, vine maple,
huckleberry, arrowwood and hazel.

From the cor. of secs. 25, 26, 35 and 36.

N. 89°32' W., bet. secs. 26 and 35.

Ascend 113 ft. over NE. slope, through timber and undergrowth.

6.99 Spur, slopes N.; desc. 370 ft. over NW. slope.

22.10 Pacific Highway, bears N. and S.; desc. 10 ft. over W. slope.

22.50 Branch, 3 lks. wide, course N.; asc. 603 ft. over E. slope.

39.83 Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate
distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground,
with brass cap marked

1 S 26
¼ S 35
1955

CS. 47/404
This Cor. moved
in 1966

from which

A red fir, 10 ins. diam., bears N. 71° E., 25 lks. dist.,
marked ¼ S 26 BT.

A red fir, 13 ins. diam., bears S. 6½° W., 45 lks. dist.,
marked ¼ S 35 BT.

Ascend 38 ft. over E. slope.

41.43 Ridge, bears N. 30° E. and S. 30° W.; desc. 814 ft. over NW. slope.

61.33 Stream, 10 lks. wide, course N. 20° E.; asc. 651 ft. over SE. slope.