

Dependent Resurvey, Portion of Subdivisional Lines, T. 32 S., R. 5 W.

CHAINS

A sawed fir stump, 16 ins. diam., bears S. 76° E., 68 lks. dist., marked S 12 CS BT.

A fir, 20 ins. diam., bears S. 60° W., 75 lks. dist., marked S 11 CS BT.

A fir snag, 12 ins. diam., bears N. 35° W., 138 lks. dist., marked S 2 CS BT.

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground, with brass cap marked

FOOKPER HULL
M 107-39 1-89

T 32	S R	5 W
S 2	S 1	
<hr/>		
S 11	S 12	
1955		

from which new bearing trees

A white fir, 13 ins. diam., bears N. 32½° E., 114 lks. dist., marked T 32 S R 5 W S 1 BT.

A red fir, 10 ins. diam., bears S. 42° E., 109 lks. dist., marked T 32 S R 5 W S 12 BT.

A red fir, 18 ins. diam., bears S. 33° W., 90 lks. dist., marked T 32 S R 5 W S 11 BT.

A red fir, 9 ins. diam., bears N. 61½° W., 104 lks. dist., marked T 32 S R 5 W S 2 BT.

Reset pipe alongside the iron post.

N. 0°01' E., bet. secs. 1 and 2.

Ascend 62 ft. over SW. slope, through timber and undergrowth.

19.81 Point for the south 1/16 sec. cor. of secs. 1 and 2.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap marked

S 1/16
S 2 S 1
1955

FD BC & 3 BTs
9/2018 R. QUIMBY
M174-61

from which

A white fir, 10 ins. diam., bears S. 16° E., 41 lks. dist., marked S 1/16 S 1 BT.

A white fir, 13 ins. diam., bears N. 83½° W., 20 lks. dist., marked S 1/16 S 2 BT.

Descend 11 ft. along W. slope.

24.15 Stream, 10 lks. wide, course SW.; asc. 176 ft. over SE. slope.

39.62 Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap marked

1/4
S 2 S 1
1955

from which