

Dependent Resurvey, Portion of Subdivisional Lines, T. 32 S., R. 5 W.

CHAINS

A red fir, 42 ins. diam., bears S.  $61\frac{1}{4}^{\circ}$  E., 70 lks. dist., marked  $\frac{1}{4}$  S 1 BT.

A red fir, 20 ins. diam., bears S.  $20^{\circ}$  W., 62 lks. dist., marked  $\frac{1}{4}$  S 2 BT.

Ascend 228 ft. over SE. slope.

64.14 Spur, slopes SE.; desc. 23 ft. over NE. slope.

66.51 Branch, 1 lk. wide, course S.  $60^{\circ}$  E.; asc. 312 ft. over SE. slope.

79.24 The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., described in the field notes of the dependent resurvey of T. 31 S., R. 5 W., of this group.

Land, mountainous.

Soil, rocky clay.

Timber, fir, maple, cedar and madrona; undergrowth, vine maple, huckleberry, arrowwood and hazel.

From the cor. of secs. 1, 2, 11 and 12.

N.  $89^{\circ}37'$  W., bet. secs. 2 and 11.

Descend 51 ft. over W. slope, through timber and undergrowth.

6.54 Branch, 5 lks. wide, course S.  $30^{\circ}$  E.; asc. 85 ft. over SE. slope.

20.55 Point for the east  $\frac{1}{16}$  sec. cor. of secs. 2 and 11.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap marked

FD BC AND 2 BTS

E  $\frac{1}{16}$   $\frac{S}{S}$   $\frac{2}{11}$   
1955

9/2018 R QUIMBY

M174-61

from which

A fir, 10 ins. diam., bears S.  $25^{\circ}$  E., 46 lks. dist., marked E  $\frac{1}{16}$  S 11 BT.

A fir, 18 ins. diam., bears N.  $40^{\circ}$  W., 35 lks. dist., marked E  $\frac{1}{16}$  S 2 BT.

Ascend 44 ft. over SE. slope.

25.77 Spur, slopes S.; desc. 133 ft. over SW. slope.

38.64 Pacific Highway, bears N.  $20^{\circ}$  W. and S.  $20^{\circ}$  E.

40.80 Branch, 3 lks. wide, course S.  $20^{\circ}$  W.; asc. 10 ft. over SE. slope.

41.10 The  $\frac{1}{4}$  sec. cor. of secs. 2 and 11, perpetuated by an axle shaft,  $1\frac{1}{2}$  ins. diam., 10 ins. above ground, set by the County Surveyor in 1951.

from which bearing trees marked by the Sounty Surveyor:

A fir, 20 ins. diam., bears S.  $2\frac{1}{4}^{\circ}$  E., 59 lks. dist., marked  $\frac{1}{4}$  S CS BT.

A cedar, 14 ins. diam., bears S.  $43^{\circ}$  W., 62 lks. dist., marked  $\frac{1}{4}$  S CS BT.

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap marked