

Dependent Resurvey, Portion of Subdivisional Lines, T. 32 S., R. 5 W.

CHAINS

$\frac{1}{4} \frac{S}{S} \frac{2}{11}$   
1955

from which new bearing trees

An alder, 12 ins. diam., bears N. 19° E., 18 lks. dist.,  
marked  $\frac{1}{4}$  S 2 BT.

A white fir, 18 ins. diam., bears S. 1 $\frac{1}{2}$ ° W., 91 lks. dist.,  
marked  $\frac{1}{4}$  S 11 BT.

N. 89°42' W., beginning new measurement.

Ascend 360 ft. over E. slope.

15.83 Spur, slopes N.; desc. 191 ft. over NW. slope.

21.78 Branch, 2 lks. wide, course N. 10° W.; asc. 383 ft. over NE. slope.

40.84 The cor. of secs. 2, 3, 10 and 11, perpetuated by an iron pipe,  
1 in. diam., 10 ins. above ground, set by the County Surveyor in  
1952.

from which bearing trees marked by the County Surveyor:

A fir, 16 ins. diam., bears N. 68 $\frac{1}{4}$ ° E., 95 lks. dist.,  
marked S 2 CS BT.

A fir, 32 ins. diam., bears S. 86°45' E., 48 lks. dist.,  
marked S 11 CS BT.

A fir, 30 ins. diam., bears S. 34 $\frac{1}{4}$ ° W., 55 lks. dist.,  
marked S 10 CS BT.

A fir, 28 ins. diam., bears N. 31 $\frac{1}{2}$ ° W., 54 lks. dist.,  
marked S 3 CS BT.

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground,  
with brass cap marked

T 32 S R 5 W  
 $\frac{S}{S} \frac{3}{10} | \frac{S}{S} \frac{2}{11}$   
1955

from which new bearing trees

A red fir, 14 ins. diam., bears N. 56° E., 123 lks. dist.,  
marked T 32 S R 5 W S 2 BT.

A red fir, 24 ins. diam., bears S. 29° E., 96 lks. dist.,  
marked T 32 S R 5 W S 11 BT.

A white fir, 16 ins. diam., bears S. 35° W., 172 lks. dist.,  
marked T 32 S R 5 W S 10 BT.

A red fir, 50 ins. diam., bears N. 54 $\frac{1}{2}$ ° W., 132 lks. dist.,  
marked T 32 S R 5 W S 3 BT.

Reset pipe alongside the iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, maple, cedar and madrona; undergrowth, vine maple,  
huckleberry, arrowwood and hazel.