CHAINS	
37.81	Ridge, bears N. and S.; desc. 97 ft. over W. slope.
40.41	Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron posr, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap marked $\frac{1}{4}\ \frac{S\ 3}{S\ 10}$ 1955 from which
	A red fir, 25 ins. diam., bears N. 13° E., 58 lks. dist., marked ¼ S 3 BT.
	A red fir, 20 ins. diam., bears S. 41½° W., 24 lks. dist., marked ¼ S 10 BT.
	Descend 411 ft. over W. slope.
57.38	Branch, 1 lk. wide, course N. 30° W.; asc. 21 ft. over NE. slope.
69.63	Top of ascent on N. slope; desc. 286 ft. over NW. slope.
80.82	The cor. of secs. 3, 4, 9 and 10, determined at record bearing and distance from two of the original bearing trees:
	A fir, 50 ins. diam., bears S. 50° W., 30 lks. dist., with marks S 9 BT uncovered.
	A madrona, 10 ins. diam., bears N. 60° W., 12 lks. dist., with marks S 4 uncovered.
	At the corner point
	Set an iron post, 36 ins. long, 2 ins. diam., 30 ins. in the ground, with brass cap marked T 32 S R 5 W S 4 | S 3 S 9 | S 10 1955 from which new bearing trees
	A fir, 24 ins. diam., bears N. 71¼° E., 93 lks. dist., marked T 32 S R 5 W S 3 BT.
	A fir, 9 ins. diam., bears S. 36¼° E., 18 lks. dist., marked T 32 S R 5 W S 10 BT.
	A fir, 18 ins. diam., bears S. 72° W., 115 lks. dist., marked T 32 S R 5 W S 9 BT.
	A fir, 12 ins. diam., bears N. 36¼° W., 70 lks. dist., marked T 32 S R 5 W S 4 BT.
	Land, mountainous. Soil, rocky clay. Timber, fir, maple, cedar and madrona; undergrowth, vine maple, huckleberry, arrowwood and hazel.
	N. 0°32' W., bet. secs. 3 and 4.
	Descend 237 ft. along W. slope, through timber and undergrowth.
13.54	Branch, 4 lks. wide, course N. 80° W.; asc. 82 ft. along W. slope.