

Portion of the Subdivisional Lines of Sec. 2, T. 32 S., R. 5 W.

CHAINS

from which

A white fir, 9 ins. diam., bears S. 44° E., 20 lks. dist., marked CS 1/16 S 2 BT.

A madrona, 6 ins. diam., bears S. 4½° W., 35 lks. dist., marked CS 1/16 S 2 BT.

Ascend 205 ft. along W. slope.

38.88 Top of ascent on W. slope; descend 11 ft. along W. slope.

39.44 Point for the center ¼ sec. cor. of sec. 2, at intersection with the E. and W. center line.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap marked

C ¼ S 2  
1955

from which

A red fir, 31 ins. diam., bears S. 37° E., 4 lks. dist., marked C¼ S 2 BT.

A red fir, 18 ins. diam., bears S. 59° W., 8 lks. dist., marked C¼ S 2 BT.

Descend 36 ft. along W. slope.

40.84 Draw, drains S. 80° W.; asc. 109 ft. along W. slope.

57.07 Spur, slopes W.; desc. 162 ft. over NW. slope.

72.27 Branch, 3 lks. wide, course N. 80° W.; desc. 39 ft. along W. slope.

79.26 The ¼ sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., described in the field notes of the dependent resurvey of T. 31 S., R. 5 W., of this group.

Land, mountainous.

Soil, rocky clay.

Timber, fir, maple, cedar and madrona; undergrowth, vine maple, huckleberry, arrowwood and hazel.

From the ¼ sec. cor. of secs. 1 and 2.

N. 89°48' W., along the E. and W. center line of sec. 2.

Ascend 288 ft. over SE. slope, through timber and undergrowth.

20.19 Point for the center east 1/16 sec. cor. of sec. 2.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap marked

FD BC

MKD -2 NEW BTs

9/2018

R. QUIMBY

M174-61

C  $\frac{E\ 1/16}{S\ 2}$  C  
1955

from which

A cedar, 18 ins. diam., bears S. 28° E., 83 lks. dist., marked CE 1/16 S 2 BT.

A cedar, 20 ins. diam., bears N. 37° E., 58 lks. dist., marked CE 1/16 S 2 BT.

Ascend 365 ft. over SE. slope.