

Survey No. 792

CHAINS

A shake stable, the northeast corner of which bears from Cor. No. 2 Tom Boy lode, S. 39°40' W., 179.5 ft., 12 x 14 ft.; course of long sides N. and S.

A log cabin, the northeast corner of which bears from Cor. No. 2 Tom Boy lode, S. 40°37' W., 120.6 ft., 14 x 16 ft.; course of long sides N. 23° E.

A shake machinery building, the northwest corner of which bears from Cor. No. 2 Tom Boy lode, S. 20° E., 73 ft., 18 x 30 ft.; Course of long sides North and South.

All belong to claimants herein.

INSTRUMENT

This survey was made with a Berger & Sons mining transit No. 5008. The courses were deflected from the true meridian as determined by direct solar observations. The distances were measured with 100 and 500 ft. steel tapes.

REPORT.

The lode line of each location of this claim was run directly upon the ground, and the several corners established by means of offsets from the lode lines. All lines were run either directly on the ground, or by traverses, run upon the ground and submitted in a separate report herewith.

The south corner of secs. 33 and 34, T. 31 S., R. 2 W. of W. M. is a porphyry stone, 10 x 12 ins., 6 ins. above ground, chiseled with 3 notches on the E. and W. edges. Near it are 2 witness trees, blazed and scribed T 31 S R 2 W S 34 BT and T 31 S R 2 W S 33 BT.

The S. $\frac{1}{4}$ sec. cor. of sec. 4, T. 32 S., R. 2 W. of W. M. is a porphyry stone, 8 x 9 ins., 6 ins. above ground, chiseled $\frac{1}{4}$ on N. face. Near it are two bearing trees blazed and scribed $\frac{1}{4}$ S 4 BT and $\frac{1}{4}$ S 9 BT.

The SW. cor. of sec. 4, T. 32 S., R. 2 W. of W. M. is a porphyry stone, 6 x 7 ins., 5 ins. above ground, chiseled with 5 notches on S. and 4 notches on E. edge. Near it are 2 bearing trees blazed and scribed T 32 S R 2 W S 4 BT and T 32 S R 2 W S 5 BT.

The W. $\frac{1}{4}$ sec. cor. of sec. 4, T. 32 S., R. 2 W. of W. M. is an andesite stone, 7 x 8 ins., 6 ins. above ground, chiseled $\frac{1}{4}$ on W. face. Near it are 2 witness trees blazed and scribed $\frac{1}{4}$ S 4 BT and $\frac{1}{4}$ S 5 BT.

The E. $\frac{1}{4}$ sec. cor. of sec. 4, T. 32 S., R. 2 W. of W. M., is an andesite stone, 8 x 11 ins., 10 ins. above ground, chiseled $\frac{1}{4}$ on W. face, with mound of stone, 3 ft. base, 2 ft. high, W. of cor.

The disagreements between the courses and distances of this survey and those of the amended location certificates are due to errors in the latter.

In order to save time and avoid great expense in taking assistants before a Notary Public, it was necessary for me to administer the oaths to assistants.