

## Survey No. 883

CHAINS Feet	
1066.50	Spur of ridge, slopes N. 10° E.; along northwesterly slope.
1346.50	Cor. No. 4, Elsie lode of this survey.
1481.00	Cor. No. 3.
	Set a tan oak post, 66 ins. long, 5 ins. sq., 24 ins. in the ground, and in a mound of earth, for Cor. No. 3, mkd. G-3-G S-4-883; from which
	A fir, 28 ins. diam., bears N. 45°00' W., 11.5 ft. dist., mkd. G-3-G S-4-883 BT.
	A fir, 28 ins. diam., bears S. 11°45' W., 12.8 ft. dist., mkd. G-3-G S-4-883 BT.
	Thence N. 24°09' W.
	Descend northwesterly slope.
300.00	Lode line; discovery point bears N. 67°06' E., 981 ft. dist.
600.00	Cor. No. 4.
	Set a tan oak post, 66 ins. long, 4 ins. sq., 24 ins. in the ground, and in a mound of earth, for Cor. No. 4, mkd. G-4-G S-3-883; from which
	A hemlock, 10 ins. diam., bears N. 40°00' W., 3.6 ft. dist., mkd. G-4-G S-3-883 BT.
	A hemlock, 9 ins. diam., bears S. 47°10' W., 16.4 ft. dist., mkd. G-4-G S-3-883 BT.
	Thence N. 67°06' E.
	Along northwesterly slope.
1250.00	Ridge, course N. 40° E. and S. 40° W.; descend southeasterly slope.
1481.00	Cor. No. 1, and place of beginning.

## GRANADA SW. LODE

Beginning at Cor. No. 1 of the Granada SW. lode, identical with the southeasterly corner of the Granada SW. No. 2 lode, unsurveyed, and claimant same as claimant herein, where I

Set a tan oak post, 66 ins. long, 4 ins. sq., 24 ins. in the ground, and in a mound of earth, for Cor. No. 1, mkd. G S-1-883; from which

    The  $\frac{1}{4}$  sec. cor. bet. secs. 33 and 34, T. 29 S., R. 2 W., W. M., bears S. 33°09'19" E., 874.20 ft. dist.; an iron post, 1 in. diam., 10 ins. above ground, firmly set, with brass cap mkd. and witnessed as described in the official record.

    The southwesterly corner of the Granada SW. No. 2 lode, unsurveyed, bears S. 67°06' W., 1500 ft. dist.

    A fir, 28 ins. diam., bears N. 26°30' W., 16.0 ft. dist., mkd. G S-1-883 BT.

    A cedar, 20 ins. diam., bears S. 87°45' E., 13.2 ft. dist., mkd. G S-1-883 BT.

        Thence N. 24°09' W.

Descend northwesterly slope.