

11946 County Surveyor's Record, Douglas County, Oregon

Survey No. 916

CHAINS Feet	The magnetic declination at this corner is 19°07' E.  Thence S. 52°47'30" E.
315.58	Lode line; discovery point bears S. 18°06' W., 585.49 ft. dist.
516.93	Cor. No. 3.  Set a galvanized iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd. CD-3-916; from which  A fir, 18 ins. diam., bears N. 40°30' W., 6.9 ft. dist., mkd. CD-3-916 BT.  A fir, 16 ins. diam., bears S. 30°15' E., 24.8 ft. dist., mkd. CD-3-916 BT.  A corner of the location bears N. 16°01'30" E., 158.60 ft. dist.  The magnetic declination at this corner is 19°29' E.  Thence S. 16°01'30" W.
370.00	Center of Hogum Creek, 6 ft. wide, course N. 85° W.
1,493.86	Intersect line 3-5 Sur. No. 5 Green Mountain Quartz Mine lode, approved July 8, 1887, at a point from which Cor. No. 5 bears S. 56°08' E., 290.9 ft. dist.
1,500.00	Cor. No. 4.  Set a galvanized iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd. CD-4-916; from which  A fir, 36 ins. diam., bears S. 62°00' W., 12.6 ft. dist., mkd. CD-4-916 BT.  A fir, 18 ins. diam., bears North, 31.5 ft. dist., mkd. CD-4-916 BT.  Cor. No. 5 Sur. No. 5, Green Mountain Quartz Mine lode, approved July 8, 1887, bears S. 57°17'30" E., 289.08 ft. dist.  Cor. No. 3 Sur. No. 5 Green Mountain Quartz Mine lode, approved July 8, 1887, bears N. 55°12' W., 295.11 ft. dist.  The magnetic declination at this corner is 20°44' E.  Thence N. 52°47'30" W.
101.19	Intersect line 3-5 Sur. No. 5 Green Mountain Quartz Mine lode, approved July 8, 1887, at a point from which Cor. No. 5 bears S. 56°08' E., 390.03 ft. dist.
200.00	Center of Robert Dollar Co.'s road, 50 ft. wide, bears N. 45° W. and S. 45° E.
258.72	Lode line; discovery point bears N. 18°06' E., 894.81 ft. dist.
430.00	Center of Robert Dollar Co.'s road, bears N. 80° E., and S. 80° W.
574.30	Cor. No. 1, and place of beginning.

AREAS

	Acres
Total area, Cloudy Day lode -----	17.520
Area in conflict with Sur. No. 5 Green Mountain Quartz Mine lode, approved July 8, 1887 -----	0.007