

# 11980 County Surveyor's Record, Douglas County, Oregon

4

HOMESTEAD ENTRY SURVEY NO. 129  
 METES AND BOUNDS SURVEY OF MARSHEL WAGGONER, HOMESTEAD ENTRY  
 SIUSLAW NATIONAL FOREST, OREGON.

CHAINS

Thence

S. 84°00' W., on true line to Cor. 6, along S. side of road exemption.

Over rolling land, through heavy timber and dense undergrowth.

1.00 Leave rolling and enter level land, bears NW. and SE.

2.00 Creek, 4 lks. wide, course SW.

13.50 Harvey Creek, 40 lks. wide, course NW.

17.60 Dry wash, course NW.

21.17 To Cor. No. 6.

In place of temp. stake, I set a sandstone, 26 x 14 x 6 ins., 16 ins. in the ground, for Cor. 6, mkd. 6 H E S 129 on S. face, with a cross (X) on top; from which

A fir, 12 ins. diam., bears S. 10°45' E., 19½ lks. dist.,

A fir, 6 ins. diam., bears S. 54°45' W., 65 lks. dist.,  
 both trees blazed and scribed 6 H E S 129 BT.

Land, rolling and level.

Timber, fir, maple and alder.

Soil, 1st rate.

July 31, 1914, at a point near Cor. 3, I set off 18°21' N. on the decl. arc, and at apparent noon, I observe the sun on the meridian; the resulting lat. is 43°42' N.

July 31, 1914.

August 1, 1914.

Thence

N. 74°42' W., on true line to Cor. 7, along south side of road exemption.

Over level land, through heavy timber and dense undergrowth.

1.25 Harvey Creek, 40 lks. wide, course SW.

10.00 Dry wash, course SW.

16.50 Dry wash, course SW.

18.00 Leave timber and undergrowth, bears N. and S. Enter cultivation, bears N. and S.

22.26 Fence, bears NE. and SW.

27.98 To Cor. No. 7.

In place of temp. stake I set a sandstone, 28 x 10 x 8 ins., 18 ins. in the ground, for Cor. 7, mkd. 7 H E S 129 on S. face, with a cross (X) on top; from which

An alder, 9 ins. diam., bears S. 46°20' E., 279 lks. dist.,

An alder, 10 ins. diam., bears S. 41°05' E., 277 lks. dist.,  
 both trees blazed and scribed 7 H E S 129 BT.

Land, level.

Timber, fir, alder and maple.

Soil, 1st rate.