

HOMESTEAD ENTRY SURVEY NO. 130
 SIUSLAW NATIONAL FOREST
 OREGON

CHAINS

N. 88°32' E., on a true line, along the N. bdy. of sec. 6, T. 22 S., R. 10 W.

Over mountainous land, through scattering fir, cedar and maple timber and dense undergrowth.

Descend.

- .40 Creek, 1 lk. wide, course SE., 20 ft. below cor.; ascend.
- 1.10 Spur, 15 ft. above creek, slopes S.; descend.
- 1.73 Creek, 2 lks. wide, course SW., 15 ft. below spur; ascend.
- 9.03 Again make diligent search for traces of closing cor. of T. 21 S., Rs. 10 and 11 W., but find none.
- 10.00 Top of ridge, bears NW. and SE., 260 ft. above creek; descend.
- 20.50 Leave mountainous and enter level land, 150 ft. below ridge.
- 19.90 Fall 112 lks. S. 1°28' E. of Cor. No. 1 of listing survey, identical with what has been considered by settlers in the vicinity as the closing cor. of T. 21 S., Rs. 10 and 11 W., which is a post, 3 ins. sq., set in a mound of stone, witnessed by two bearing trees. Old settlers inform me that about 20 years ago W. H. Byars, in a private survey, set this post and marked it for closing cor. of T. 21 S., Rs. 10 and 11 W. The bearing trees were added by the listing surveyor. I do not consider this the original closing township cor., but leave it as found.
- 20.92 Set a temporary stake for Cor. No. 25 of this survey.
- 28.49 Harvey Creek, 50 lks. wide, course SW.
- 31.43 Wagon road and telephone line, bears NE. and SW.
- 37.17 Leave level land; ascend W. slope.
- 38.50 $\frac{1}{4}$ sec. cor. on N. bdy. of sec. 6, T. 22 S., R. 10 W., heretofore described.

July 21, 1914: At this cor. I set off 20°33' N. on the decl. arc, and at 12^h 06^m, l.m.t., observe the sun on the meridian; the resulting lat. is 43°41' N.

July 21, 1914.

(Note:- By letter from the U. S. Surveyor General of Oregon to the District Forester, dated April 22, 1915, it is stated that after a careful examination of the preliminary returns it is found necessary to call upon Frank D. Maxwell, Forest Service Surveyor, to make certain corrections in the field, and to make further retracements, if necessary, to prove beyond a doubt that the cor. re-established by him as the cor. of T. 22 S., Rs. 10 and 11 W. is the authentic old corner. Frederick W. Rase, Surveyor-Forest Service, is designated by the District Forester to make the necessary corrections. The returns of his survey follow.)

Survey executed by Frederick W. Rase,
Surveyor - Forest Service

Survey commenced September 11, 1915, and executed with a Buff & Buff light mountain transit No. 9701 with solar attachment; the horizontal limb having two double verniers placed opposite to each other reading to single minutes of arc, which is also the least count of the verniers of the latitude and declination arcs.

The instrument was examined, tested on the true meridian at Portland, Oregon, found correct and was approved by the Assistant Supervisor of Surveys for Oregon and Washington, April 16, 1915.