

HOMESTEAD ENTRY SURVEY NO. 179
 UMPQUA NATIONAL FOREST
 STATE OF OREGON

CHAINS

Set a granite boulder, 24x10x7 ins., 14 ins. in the ground, over a stone marked with a cross, for cor. No. 9 of this survey, marked 9 HES 179 on side facing the claim; from which

An ash, 16 ins. dia., bears S.20°56'E., 34 lks. dist., marked X 9 HES 179 B T.

An ash, 12 ins. dia., bears N.25°15'W., 57 lks. dist., marked X 9 HES 179 B T.

Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

Thence I run

N.50°51'E., on a true line, along boundary of road exemption.

Over level land, through scattering ash, fir, hemlock, and cedar timber and undergrowth.

14.11

Cor. No. 10.

Set a granite boulder, 24x10x8 ins., 14 ins. in the ground, over a stone marked with a cross for cor. No. 10 of this survey, marked 10 HES 179 on side facing the claim; from which

An ash, 12 ins. dia., bears S.69°12'W., 36 lks. dist., marked X 10 HES 179 B T.

An ash, 16 ins. dia., bears S.65°33'W., 60 lks. dist., marked X 10 HES 179 B T.

Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. distant within the claim.

Thence I run

N.61°09'E., on a true line, along boundary of road exemption.

Over level land, through scattering ash, fir, hemlock, and cedar timber and dense undergrowth.

18.31

Cor. No. 11.

Set a granite stone, 25x8x8 ins., 15 ins. in the ground, over a stone marked with a cross for cor. No. 11 of this survey, marked 11 HES 179 on side facing the claim; from which

A yew, 8 ins. dia., bears N.89°15'W., 39 lks. dist., marked X 11 HES 179 B T.

A cedar, 16 ins. dia., bears N.25°30'W., 57 lks. dist., marked X 11 HES 179 B T.

Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

Thence I run

N.46°30'E., on a true line, along boundary of road exemption.

Over level land, through scattering ash, fir, hemlock, and cedar timber and dense undergrowth.

4.65

Cor. No. 12, on line between cor. No. 4 of Tract A and cor. No. 4 of listing survey.