

12058 County Surveyor's Record, Douglas County, Oregon

2

HOMESTEAD ENTRY SURVEY NO. 190
 SIUSLAW NATIONAL FOREST
 STATE OF OREGON

CHAINS

RETRACEMENTS

September 22, 1916: Preliminary to the survey of this Homestead Entry, I make the following retracements:

Commencing at the $\frac{1}{4}$ sec. cor. bet. secs. 3 and 10, which is a badly decayed post, marks not distinguishable, witnessed as described by the Surveyor General. (Bearing trees decayed and down.)

I reestablish this $\frac{1}{4}$ cor. in its original position as follows:

Set a sandstone, 15x10x6 ins., 10 ins. in the ground, mkd. $\frac{1}{4}$ on N. face; from which

A fir, 32 ins. dia., bears N.56°00'W., 44 lks. dist., mkd. $\frac{1}{4}$ S 3 B T (new).

A fir, 12 ins. dia., bears S.18°15'W., 51 lks. dist., mkd. $\frac{1}{4}$ S 10 B T (new).

Thence I run

S.89°45'E., retracing line bet. secs. 3 and 10.

40.30

Fall 13 lks. N. of the true point for cor. secs. 2, 3, 10, and 11, as evidenced by the alder B.T. in the NE. quadrant and the alder B T. in the SW. quadrant, which are in a decaying condition, but still show old markings.

I reestablish this sec. cor. in its original position as follows:

Set a granite stone, 16x7x6 ins., 11 ins. in the ground, mkd. with 5 notches on S. and 2 notches on E. edges; from which

A fir, 10 ins. dia., bears N.67°00'E., 31 lks. dist., mkd. T 20 S R 11 W S 2 B T (new)

A fir, 10 ins. dia., bears S.36°30'E., 38 lks. dist., mkd. T 20 S R 11 W S 11 B T (new)

A fir, 8 ins. dia., bears S.11°15'W., 35 lks. dist., mkd. T 20 S R 11 W S 10 B T (new)

A fir, 10 ins. dia., bears N.19°30'W., 16 lks. dist., mkd. T 20 S R 11 W S 3 B T (new)

(The true bearing and length of this line is S.89°34'E., 40.30 chs.)

From the $\frac{1}{4}$ sec. cor. bet. secs. 3 and 10, heretofore described, I run

South, on a random line, through center of sec. 10.

80.10

Fall 14 lks. E. of the $\frac{1}{4}$ sec. cor. bet. secs. 10 and 15, which is a post, $3\frac{1}{2}$ ins. dia., 14 ins. above ground, firmly set, mkd. and witnessed as described by the Surveyor General.

(The true bearing and length of the longitudinal $\frac{1}{4}$ sec. line is S.0°06'W., 80.10 chs.)

September 22, 1916

September 23, 1916: Commencing at the $\frac{1}{4}$ sec. cor. bet. secs. 9 and 10, an alder tree, 14 ins. dia., down and badly decayed, but still showing markings. The bearing trees described by the Surveyor General are also down.

I reestablish this $\frac{1}{4}$ cor. in its original position, digging out the decayed tree, as follows: