

12060 County Surveyor's Record, Douglas County, Oregon

4

HOMESTEAD ENTRY SURVEY NO. 190
 SIUSLAW NATIONAL FOREST
 STATE OF OREGON

CHAINS	
	Thence I run South on a true line. Desc. SW. slope, through fir and alder timber and undergrowth.
3.60	Draw, 100 ft. below cor. No. 2; asc. steep N. slope.
7.90	Top of ridge, bears NW. and SE., 200 ft. above draw; desc. SW. slope.
10.00	Cor. No. 3 (100 ft. below top of ridge). Set a basalt stone, 24x12x8 ins., 14 ins. in the ground, over a stone mkd. with a cross for cor. No. 3 of this survey, mkd. 3 HES 190 on side facing the claim; from which A fir, 12 ins. dia., bears N.21°15'E., 48 lks. dist., mkd. X 3 HES 190 B T. A fir, 26 ins. dia., bears S.31°20'E., 84 lks. dist., mkd. X 3 HES 190 B T. Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist., within the claim. September 23, 1916
	September 24, 1916: From cor. No. 3 of this survey, above described, I run West on a true line. Along steep S. slope, through fir and alder timber.
2.00	Desc. SW. slope.
14.80	Bottom of ravine, course NW., 315 ft. below cor. No. 3.
16.60	Creek bed, 3 lks. wide, course NW.
16.80	Asc. NE. slope.
20.00	Cor. No. 4 (80 ft. above ravine). Set a cedar post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, over a stone mkd. with a cross for cor. No. 4 of this survey, mkd. 4 HES 190 on side facing the claim; from which A maple, 10 ins. dia., bears S.78°00'E., 14 lks. dist., mkd. X 4 HES 190 B T. A fir, 24 ins. dia., bears N.84°00'E., 63 lks. dist., mkd. X 4 HES 190 B T. Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim. No stone available for cor.
	Thence I run South on a true line. Ascend NE. slope, through fir, alder, and maple timber.
1.50	Slope changes northwest.
10.00	Cor. No. 5 (190 ft. above cor. No. 4).