

HOMESTEAD ENTRY SURVEY NO. 190
 SIUSLAW NATIONAL FOREST
 STATE OF OREGON

CHAINS

Set a basalt stone, 30x14x8 ins., 8 ins. in the ground to bedrock over a stone mkd. with a cross, surrounded by mound of stone, for cor. No. 5 of this survey, mkd. 5 HES 190 on side facing the claim; from which

A fir, 8 ins. dia., bears S.68°15'W., 26 lks. dist., mkd.
 X 5 HES 190 B T.

A fir, 12 ins. dia., bears S.20°30'W., 23 lks. dist., mkd.
 X 5 HES 190 B T.

Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

Thence I run

West, on a random line, and at 20.35 chs. fall 9 lks. S. of the temporary stake set for 1/16 sec. cor. and cor. No. 6 of this survey.

(The true bearing and length of this line is N.89°45'W., 20.35 chs.)

Returning to cor. No. 5 of this survey, above described, I run N.89°45'W., on a true line.

Descend NW. slope, through fir and alder timber and undergrowth.

1.60 Ravine, course N., 80 ft. below cor. No. 5; ascend NE. slope.

7.50 Top, 180 ft. above ravine. Desc. NW. slope.

20.35 Cor. No. 6 (100 ft. below top)..

I destroy temporary stake and in its place

Set a cedar post, 3 ft. long, 5 ins. sq., 24 ins. in the ground, over a stone mkd. with a cross, for 1/16 sec. cor. and cor. No. 6 of this survey, mkd. 1/16 on W. face and 6 HES 190 on side facing the claim; from which

A fir, 8 ins. dia., bears N.50°17'W., 17 lks. dist., mkd.
 X 6 HES 190 1/16 B T.

A fir, 12 ins. dia., bears N.65°00'E., 48 lks. dist., mkd.
 X 6 HES 190 1/16 B T.

Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

No stone available for cor.

Sky overcast at noon; unable to make lat. obsn.

Thence I run

N.0°06'E., on a true line along the longitudinal ¼ sec. line and E. bdy. of that portion of H.E. No. 02958 lying within the surveyed W. half of sec. 10, same entryman.

Desc. N. slope, through fir and alder timber.

6.00 Bottom, 270 ft. below cor. No. 6, thence across bottom, through undergrowth.

6.21 Five Mile Creek, 10 lks. wide, course West.