

12076 County Surveyor's Record, Douglas County, Oregon

2

HOMESTEAD ENTRY SURVEY NO. 213
 SIUSLAW NATIONAL FOREST
 STATE OF OREGON

CHAINS

The magnetic bearing of the true mer. at this cor. at 10h00m a.m. is N.20°45'W.; the angle thus determined gives the mag. decl. 20°45'E. The mean mag. decl. is 20°43'E.

RETRACEMENTS AND SUBDIVISIONS

August 28, 1917: Preliminary to the survey of this homestead entry, I make the following retracements and section subdivisions:

Commencing at the meander corner on the range line between fractional secs. 6 and 1, T. 22 S., Rs. 10 and 11 W., Willamette Meridian, Oregon, which I reestablish in original position from the original bearing trees.

Set an iron pipe, 48 ins. long, 2 ins. dia., 36 ins. in the ground, with nail in wooden plug for chaining point; from which

A spruce, 24 ins. dia., bears S.8°00'E., 169 lks. dist., marked T 22 S R 10 W M C S 6 B T (original).

A spruce, 36 ins. dia., (stump only) bears S.16°00'W., 134 lks. dist., marked T 22 S R 11 W M C S 1 B T (original).

Thence I run

South (recorded bearing) retracing the range line bet. frac. secs. 6 and 1.

17.30

Fall one lk. east of cor. of secs. 1 and 12, T. 22 S., R. 11 W., which is a stone, 7x12x6 ins. above ground, loosely set, marked and witnessed as described by the Surveyor General. I set stone more firmly, chisel notches deeper, and mark X on top for chaining point.

(The true bearing and length of this line is S.0°02'W., 17.30 chs.)

Thence I run

West (recorded bearing) retracing the line bet. secs. 1 and 12.

40.33

Fall 21 lks. south of the $\frac{1}{4}$ cor. bet. secs. 1 and 12, which is a cross (X) chiseled on sandstone bedrock with $\frac{3}{4}$ north of cross, witnessed as described by Surveyor General.

(The true bearing and length of this line is N.89°42'W., 40.33 chs.)

Thence I run

West (recorded bearing) retracing the line bet. secs. 1 and 12.

40.30

Fall 20 lks. north of the cor. of secs. 11 and 12, which is a cross (X) chiseled on sandstone bedrock, marked and witnessed as described by the Surveyor General.

(The true bearing and length of this line is S.89°43'W., 40.30 chs.)

Thence, sighting to closing cor. for secs. 1 and 2, I run

S.89°43'W., on a true line.

1.16

Intersect closing cor. for secs. 1 and 2, which is a cross (X) on sandstone bedrock, marked and witnessed as described by the Surveyor General.

(The true bearing and length of this line is S.89°43'W., 1.16 chs.)