

12080 County Surveyor's Record, Douglas County, Oregon

6

HOMESTEAD ENTRY SURVEY NO. 213
SIUSLAW NATIONAL FOREST
STATE OF OREGON

CHAINS

Cor. is on steep sidehill; pits and mound impracticable.

Thence I run

N.15°33'E., on a random line (calculated bearing) and at 20.94 chs. intersect temporary stake set for cor. No. 6 of this survey on south bdy. of Lot 6.

(The true bearing and length of this line is N.15°33'E., 20.94 chs.)

Returning to cor. No. 5 of this survey, above described, I run

N.15°33'E., on a true line, along E. bdy. of road exemption (Tract C).

Along northwesterly slope of gulch, through dense undergrowth and scattering timber.

5.00 Leave side hill and continue along dry creek bed, through undergrowth.

5.22 Pass from unlisted to listed land.

12.10 Enter open level clearing.

20.94 Cor. No. 6 and meander corner, on south bdy. of Lot 6 and at mean high tide line on left bank of Umpqua River, identical with temporary stake, which I destroy and in its place

Set a sandstone, 28x24x5 ins., 18 ins. in the ground, over a stone marked with a cross for meander cor. and cor. No. 6 of this survey, marked 6 H E S 213 on side facing the claim and M C on side facing the river; from which

A spruce, 14 ins. dia., bears N.59°15'E., 6 lks. dist., marked X 6 H E S 213 M C B T.

An ash, 10 ins. dia., bears N.61°15'W., 205 lks. dist., marked X 6 H E S 213 M C B T.

Dig pit, 36x36x18 ins., 8 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, 3 $\frac{1}{4}$ ft. dist. on line southwest of corner.

Thence I run with meanders of left bank of Umpqua River, at mean high tide line, over open grassy beach.

S.60°45'E., 3.85 chs.

S.68°42'E., 3.00 " to Cor. No. 1 and place of beginning of Tract A.

TRACT B

September 1, 1917: Beginning at cor. No. 7 of this survey, at the intersection of the westerly bdy. of the road exemption with the south bdy. of Lot 6 of fractional sec. 1.

Set a sandstone, 24x12x6 ins., 14 ins. in the ground, over a stone marked with a cross for cor. No. 7 of this survey, marked 7 H E S 213 on side facing the claim.

No bearings available; therefore dig pits, 24x24x12 ins., crosswise on line southwest and west of corner, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, 3 $\frac{1}{2}$ ft. dist., within the claim.

Cor. No. 6 of Tract A of this survey, bears east 31 lks. dist.