

1208² County Surveyor's Record, Douglas County, Oregon

8

HOMESTEAD ENTRY SURVEY NO. 213
 SIUSLAW NATIONAL FOREST
 STATE OF OREGON

CHAINS

Thence I run

N.12°32'E., on a true line, over unlisted land.

Along steep easterly slope, through dense undergrowth and scattering timber.

7.10

Intersect cor. No. 9 of listing survey, which I destroy.

Cor. No. 10 of listing survey, which I destroy, bears S.17°45'E., 2.02 chs. dist.

Thence over listed land to

15.52

Cor. No. 10, identical with cor. No. 8 of listing survey, which I destroy, and in its place

Mark a sandstone boulder in place, showing 5x8x3 ft. above ground, with a cross (X) on top and 10 H E S 213 on side facing claim, for cor. No. 10 of this survey; from which

A maple, 12 ins. dia., bears S.55°00'W., 38 lks. dist., marked X 10 H E S 213 B T.

A fir, 6 ins. dia., bears S.40°30'E., 15 lks. dist., marked X 10 H E S 213 B T.

Cor. is on steep side hill; pits and mound impracticable.

Authority having been granted by G.L.O. letters of February 4 and March 30, 1914, to straighten boundaries of homestead entries where rendered unduly crooked by unnecessary exclusion and it being the desire of the Forest Service and the entryman, I run from cor. No. 10 of this survey to cor. No. 3 of listing survey, thereby eliminating 4 angle points.

From cor. No. 10 of this survey, above described, I run

N.80°30'W., on a random, on approximate calculated bearing, and at 19.46 chs. fall 12½ lks. N.9°30'E. of cor. No. 3 of listing survey.

(The true bearing and length of this line is N.80°52'W., 19.46 chs.)

Returning to cor. No. 10 of this survey, above described, I run

N.80°52'W., on a true line.

Ascend northeasterly slope, through dense undergrowth and scattered timber.

9.70

Top of ascent, 50 ft. above cor. No. 10.

Descend northwesterly slope.

18.80

Dry creek bed and gulch, 50 ft. below point of descent, course north.

Ascend east slope.

19.46

Cor. No. 11, 15 ft. above gulch, identical with cor. No. 3 of listing survey, which I destroy, and in its place

Set a sandstone, 26x10x8 ins., 16 ins. in the ground, over a stone marked with a cross for cor. No. 11 of this survey, marked 11 H E S 213 on side facing the claim; from which

A maple, 8 ins. dia., bears S.31°15'E., 23 lks. dist., marked X 11 H E S 213 B T.