

County Surveyor's Record, ¹Douglas County, Oregon

12083

Dependent Resurvey of the Line Between Sections 16 and 21,
T. 23 S., R. 7 W., W. M., Oregon.
Executed by Thomas A Tillman, Civil Engineer (Cadastral), under
Special Instructions dated Nov. 2, 1956.

CHAINS

(Restoring the 1855 survey by Thomas H. Hutchinson.)

Beginning at the cor. of secs. 16, 17, 20 and 21, which has been remonumented with an iron pipe, $\frac{1}{2}$ in. diam., 16 ins. above ground, deeply driven and firmly in place, from which the remaining original bearing tree:

A sawed fir stump, 48 ins. diam., bears S. 45° W., 127 lks. dist., with trunk of tree lying alongside; trunk bears two blazes, the upper one opened and burned, with no identifiable marks remaining; I open lower blaze and uncover scribe marks "BT".

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, over the iron pipe, which I drive into the ground until it protrudes 6 ins., with brass cap marked

T23S	R7W	S 17	S 16
S20	S 21		
1957			

FO. OK JAN. 1994
BY BENTZ M 119-24

from which new bearing trees,

A fir, 7 ins. diam., bears N. 29 $\frac{1}{2}$ ° E., 32 lks. dist., marked T23S R7W S16 BT.

A fir, 8 ins. diam., bears S. 43° E., 23 $\frac{1}{2}$ lks. dist., marked T23S R7 W S21 BT.

A fir, 10 ins. diam., bears S. 49 $\frac{3}{4}$ ° W., 61 lks. dist., marked T23S R7W S20 BT.

A fir, 7 ins. diam., bears N. 9 $\frac{1}{2}$ ° W., 36 $\frac{1}{2}$ lks. dist., marked T23S R7W S17 BT.

The sec. cor. is located in a woven wire fence row, which extends N. 70° E. and W.

S. 87° 17' E., bet. secs. 16 and 21, marking and blazing the true line.

Ascend 6 ft. over gentle W. slope, through heavy timber and dense undergrowth.

- 0.16 A fir, 8 ins. diam., on line, marked with two hacks on E. and W. sides.
- 1.05 Spur, slopes NE.; desc. 280 ft. over E. slope.
- 9.10 Branch, along edge of timber and brush, 2 lks. wide, course S. 20° E.; asc. 60 ft. over rolling SW. slope through scattering timber and clumps of brush.
- 11.70 Dirt road, bears N. and S.
- 13.60 Top of ascent on S. slope; desc. 30 ft. over SE. slope.
- 14.32 SE. cor. of Mode's barn, bears North, 75 lks. dist.
- 17.50 Spring branch, 1 lk. wide, in shallow ravine, course S.; asc. 20 ft. over west slope.
- 19.34 Point for the W. 1/16 sec. cor. of secs. 16 and 21.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 32 ins. in the ground, with brass cap marked