

Dependent Resurvey of Line Bet. Secs. 16 and 21, T. 23 S., R. 7 W.

CHAINS

A  $\frac{1}{16}$   $\frac{S 16}{S 21}$   
1957

from which

A fir, 32 ins. diam., bears N. 65° E., 222 lks. dist.,  
marked W  $\frac{1}{16}$  S16 BT.

NW. of cor. of Mode's house bears S. 19° E., 190 lks. dist.

Standpipe at watering tank, bears S. 10 $\frac{3}{4}$ ° W., 36 $\frac{1}{2}$  lks. dist.

A Black oak, 22 ins. diam., bears S. 65 $\frac{3}{4}$ ° W., 177 lks. dist.,  
marked W  $\frac{1}{16}$  S21 BT.

An iron pipe,  $\frac{1}{2}$  in. diam., 2 ins. above ground, firmly set,  
marking a previous temporary point, bears N. 62° W., 134 $\frac{1}{2}$   
lks. dist.

The  $\frac{1}{16}$  sec. cor. is located in a gravelled road, bearing generally  
NW. and SE.

Ascend 80 ft. over rolling SW. slope, through farm area.

23.30 Woven wire fence, bears N. and S.

29.60 Woven wire fence, bears N. 70° W. and S. 70° E.

31.20 Woven wire fence, bears N. and S.

32.70 Spur, slopes S.; desc. 106 ft. over general SE. slope.

34.20 Enter heavy timber and dense undergrowth; edge bears N. and S.

36.20 Dirt road, bears generally NE. and SW. winding.

38.68 The  $\frac{1}{4}$  sec. cor. of secs. 16 and 21, determined by reference to the  
remaining original bearing tree:

A fir, 36 ins. diam., bears N. 34° E., 13 lks. dist.; I find no  
scribe marks after opening scars which appear to be upper and  
lower blazes cut into about 40 years ago and again overgrown  
after being burned; according to a signed statement furnished  
me by Frank Kausche, hereto appended, the scribe marks were  
visible at that time. I accept this tree as the best avail-  
able evidence of the original corner.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the  
ground, with brass cap marked

FD. OK JAN. 1994  
BY BENTZ M119-24

T23S R7W  
 $\frac{1}{4}$   $\frac{S 16}{S 21}$   
1957

from which new bearing trees:

A fir, 6 ins. diam., bears N. 46 $\frac{1}{2}$ ° W., 32 lks. dist.,  
marked  $\frac{1}{4}$  S 16 BT.

A fir, 16 ins. diam., bears S. 35° W., 40 lks. dist.,  
marked  $\frac{1}{4}$  S21 BT.

N. 87° 34' E., beginning new measurement.

Descend 25 ft. over SE. slope, along S. edge of logged area.