

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Line Bet. Secs. 16 and 21, T. 23 S., R. 7 W.

CHAINS

- 0.90 Small ravine, course S.; asc. 30 ft. over SW. slope.
- 2.80 Top of ascent on S. slope; desc. 170 ft. over SE. slope.
- 13.80 Creek, 4 lks. wide, in bed 10 lks. wide, course N. 60° E., bending to E.; asc. 70 ft. along steep, bluffy N. slope.
- 18.80 Top of ascent on N. slope; desc. 150 ft. along steep N. slope.
- 27.00 Foot of descent on N. slope; asc. 50 ft. over broken NW. slope.
- 31.50 Spur, slopes N. 10° E.; Desc. 122 ft. over NE. slope.
- 35.27 Foot of slope, bears N. 30° W. and S. 30° E., along edge of bottom. Point for the meander cor. of secs. 16 and 21, on the left bank of the Umpqua River, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam.; 24 ins. in the ground, with brass cap marked

*Fd. OK JAN. 1994  
By BENTZ M119-24*

T23S  
S 16  
—  
S 21  
R7W  
1957

from which

A myrtle, 12 ins. diam., bears N. 7° W., 35 lks. dist., marked T23S R7W S16 MC BT.

A fir, 48 ins. diam., bears S. 83° W., 64 lks. dist., marked T23S R7W S21 MC BT.

Descend 10 ft. over bottom land.

- 35.90 Over grown logging road, bears N. 25° W. and S. 25° E.
- 36.00 Top of river bank, bears N. 25° W. and S. 25° E.; desc. 40 ft. over E. slope.

- 37.70 Left edge of Umpqua River, 6 chs. wide at present low water stage, course N. 20° W. Thence in river.

- 39.82 True point for the cor. of secs. 15, 16, 21 and 22, at proportionate distance, falls in river.

From this point the ¼ sec. cor. of secs. 15 and 16, bears N. 2° 56' E., 40.91 chs. dist., monumented with the original oak post, 27 ins. long, 3½ ins. square, protruding 20 ins. above ground, marked ¼ S on SW. side, somewhat loose due to decay, but still solid, from which the remains of one of the original bearing trees:

A stump hole containing pieces of burl and decayed wood, bears N. 75° E., 243 lks. dist.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked

T23S R7W  
¼  
S 16 | S 15  
|  
1957

*Fd. OK Jun. 1994  
By Bentz m 119-24*

from which new bearing trees:

A fir, 40 ins. diam., bears S. 18¼° E., 261 lks. dist., marked ¼ S 15 BT. This tree is located at N. side of a trail bears E. and W.